



**MedDream PACS**

**USER'S MANUAL**

**(version 6.5.2)**

---

---

© 2016, Softneta UAB, Kaunas

All rights reserved in the event of granting of patents or registration as a utility patent.

All names of companies and products mentioned in this user`s manual may be trademarks or registered trademarks. References to products of other manufacturers are for information purposes only. Such references are intended neither as an approval nor a recommendation of these products. Softneta UAB accepts no liability for the performance or use of such products.

Other brand names, software and hardware names used in this user`s manual are subject to trademark or patent protection. The quoting of products is for informational purposes only and does not represent a trademark misuse.

This user`s manual is protected by copyright. Unless expressly authorized in writing, dissemination, duplication or other commercial exploitation of this documentation set or communication of its contents or parts of it is not permitted. In case of infringement, the violator may be liable to pay compensation for damages.

Specifications due to technical developments are subject to change. This user`s manual is not subject to the revision service. Please contact the manufacturer or authorized dealer to request the latest edition of the manual.

---

---

# Table of Contents

<b>TABLE OF CONTENTS</b> .....	<b>3</b>
<b>NOTES ON THE USER`S MANUAL</b> .....	<b>6</b>
Purpose and availability of documentation .....	6
Questions and comments.....	6
Explanation of symbols used.....	7
<b>INTRODUCTION</b> .....	<b>8</b>
<b>GLOSSARY</b> .....	<b>9</b>
<b>CHANGE LOG</b> .....	<b>10</b>
<b>PLATFORMS</b> .....	<b>14</b>
<b>INSTALLATION</b> .....	<b>15</b>
<b>MANAGING MEDDREAM PACS USER ACCOUNTS</b> .....	<b>16</b>
Privacy Attributes .....	16
Creating New User Accounts .....	17
Creating Group User Accounts .....	20
Deleting Existing User Accounts .....	20
Modifying Existing User Accounts.....	21
<b>SYSTEM CONFIGURATION</b> .....	<b>22</b>
<b>SMTP SERVER CONFIGURATION</b> .....	<b>26</b>
<b>SYSTEM JOURNAL LOG</b> .....	<b>27</b>
Automatic Monthly System Journal Log Emails .....	28
Automatic Purging Aged System Journal Log.....	28
<b>APPLICATION ENTITY TABLE</b> .....	<b>29</b>
SCU Application Entities .....	32
SCP Application Entities .....	34
Modality Worklist SCP Application Entities: .....	35
Query/Retrieve SCP Application Entities: .....	36
AE Group Settings: .....	37

---

<b>HL7 APPLICATIONS (OPTIONAL)</b> .....	<b>38</b>
<b>SEARCHING MEDDREAM PACS DATABASE</b> .....	<b>39</b>
<b>NAVIGATING MEDDREAM PACS WEB USER INTERFACE</b> .....	<b>40</b>
Login Page.....	40
Home Page (Today's Study Page).....	41
Main Menu Bar.....	41
Unread Studies Page.....	42
Browse Page.....	42
Study Page.....	43
Series Page.....	45
Study Notes Page.....	46
Structured Reports.....	47
Image Page (Thumbnail).....	48
Image Page (Full Size).....	49
Image Notes Page.....	50
Online Image Processing Page.....	52
Tools Page.....	53
Custom Data Element Coercion.....	53
Exporting Patients/Studies.....	55
Importing External Patients/Studies.....	56
Statistics Reports.....	57
Automatic Purging Archive Directories.....	58
Check Duplicate Patient IDs.....	60
Today's Log File.....	62
Upload Dicom Image.....	63
Matching ORM Message (Optional).....	63
Database Integrity Check.....	64
Import Worklist.....	64
Live Monitor (for System Administrator only).....	65
Patient Reconciliation.....	66
Anonymization Templates.....	66
Transcription Templates (Windows platforms only).....	68
Restart Service.....	69

---

---

Profile Page.....	69
Modality Worklist Page.....	70
Enter New Worklist Page .....	71
<b>FORWARDING IMAGES .....</b>	<b>71</b>
<b>POST-RECEIVE IMAGE COMPRESSION .....</b>	<b>73</b>
<b>AUTOMATIC ROUTING .....</b>	<b>75</b>
Dicom Image Routing.....	75
HL7 Message Routing (optional).....	79
<b>PRINTING IMAGES.....</b>	<b>80</b>
<b>JOB STATUS PAGE .....</b>	<b>82</b>
<b>FIGURES .....</b>	<b>83</b>
<b>TABLES.....</b>	<b>85</b>
<b>INDEX.....</b>	<b>86</b>

---

## Notes on the user`s manual

### Purpose and availability of documentation

This user`s manual describes the operation with MedDream PACS software.

Correct operation of the system is imperative for its safe and successful functioning. You should therefore ensure that you are thoroughly familiar with the user manual before setting up and using MedDream PACS for the first time.

The user manuals and other documentation enclosed with MedDream PACS should be kept accessible to users at all times to ensure that the information required for the use of MedDream PACS is readily available.

MedDream ToPACS is not intended to replace skilled and qualified medical professional. The software should only be used by people who have been trained and is acquainted with its functions, capabilities and limitations.

Users must be aware that the quality, accuracy and correctness of the output data displayed on the screen, printed or sent from MedDream PACS depends on the quality, accuracy and correctness of the input data, the user`s interface with the data, the quality, calibration and other parameters of printer or monitoring device.

MedDream PACS has been tested extensively, however, it is possible that errors may remain/emerge in the software. Users must be aware of the potential for errors and in case of an error or for other assistance, please contact Softneta UAB Customer support:

- write an e-mail [support@softneta.com](mailto:support@softneta.com)

### Questions and comments

If you have any questions or comments regarding this user`s manual, please contact Softneta UAB Customer support.

## Explanation of symbols used

The symbols used in this daily workflow refer to important safety information which warn against possible health risks or fatal injuries and contain useful notes. Whenever you see these symbols, read the accompanying information carefully and observe all safety notes and information in the user manual, daily workflow and on the device labels.

### WARNING

Indicates a hazardous situation which may result in a fatal or serious bodily injury if the appropriate safety precautions are not heeded.



### CAUTION

Indicates a hazardous situation which may result in a minor injury if the appropriate safety precautions are not heeded.



### CAUTION – DAMAGE

Indicates possible damage if the appropriate safety precautions are not heeded.



Information, hints and advice for a better understanding of the instructions to be observed in the operation of the instrument.

---

## Introduction

MedDream PACS is a DICOM 3.0 compliant PACS. Server provides connectivity to all DICOM modalities (CT, MR, CR, DX, US, etc.). Retrieving of DICOM images can be done using MedDream WEB DICOM Viewer or any DICOM enabled third party workstation.

### Features

- Fully compatible with DICOM 3.0 protocol.
- Supported storage(C-STORE), query(C-FIND), retrieval(C-GET), and transfer(C-MOVE) services
- Web-based administration. User access control
- Implicit Little Endian, Explicit Little Endian, JPEG, JPEG-LS and RLE Transfer Syntaxes supported
- Automatic image routing
- Synchronization with Remote Studies
- MedDream WEB Viewer.
- HL7 Interface (optional)
- One year technical support

MedDream PACS consists of the following components:

- A DICOM protocol server for servicing requests for image storage, query and retrieval, forwarding, routing, printing images, and Dicom-formatted media interchange through import and export functions.
- MySQL or Oracle databases for managing image records and related patient, study, series information.
- Apache 2.x HTTP server and PHP scripting engine for presenting a web-based user interface for browsing and managing database records.
- ImageMagick PHP module for displaying Dicom images through client's web browsers.
- An optional HL7 Message Listener module for receiving and sending HL7 messages via Lower-Level Transport Protocol (LLTP)

**WARNING!** *MedDream PACS cannot guarantee the accuracy of calibration data received from the modality. Moreover, Softneta cannot guarantee that the manual calibration which is performed by users is done accurately.*

---

## Glossary

AE	Application Entity
AET	Application Entity Title
PACS	Picture Archive and Communication System
DICOM	Digital Imaging and Communications in Medicine
DMWL	Dicom Modality Worklist
FSC	File Set Creator
FSR	File Set Reader
HIPAA	Health Insurance Portability and Accountability Act
HL7	Health Level Seven
HTML	Hyper-Text Mark-up Language
HTTP	Hyper Text Transfer Protocol
LUT	Look Up Table
PHP	PHP: Hypertext Preprocessor
NEMA	National Electrical Manufacturers Association
NNTLM	(NT LanMan) is an authentication process that's used by all members of the Windows NT family of products
SCP	Service Class Provider
SCU	Service Class User
SMTP	Simple Mail Transfer Protocol
SOP	Service-Object Pair
SR	Structured Report
UID	Unique ID
UNC	Universal Naming Convention

## Change log

Nr.	Version	Date	Reason
1.	1.0	1/3/2004	Initial version
2.	1.1	2/29/2004	Add section about Referring/Reading Physician Name matching for private patients/studies
3.	1.2	5/28/2004	Add sections for new features including DICOM Structured Report, Modality Worklist Management
4.	1.3	7/15/2004	Add sections for new features including exporting patients/studies to and importing external patients/studies from DICOM Media Storage Formatted media, custom data element coercion rules
5.	1.4	7/30/2004	Add support for importing external raw image files without DICOMDIR directory record
6.	1.5	9/18/2004	Add section for Automatic Purging Archive Directories
7.	1.6	10/8/2004	Add section for Automatic Image Routing by Key Attributes
8.	1.7	2/8/2005	Add section for printing to Dicom printers
9.	1.8	4/5/2005	Add section for remote study synchronization
10.	1.9	5/31/2005	Add option to move aged studies to a destination folder when running automatic study purge
11.	1.10	7/10/2005	Add Routing By Schedule Window; Add option to compress exported content into ZIP files
12.	1.11	8/18/2005	Add Statistics Reports, System Journal Log, SMTP Server Configurations
13.	1.12	11/6/2005	Added Study/Image Notes, Upload privilege, Duplicate Patient ID Resolution page
14.	3.1.8	1/14/2006	Update document revision numbering scheme; Add System Configuration Page
15.	4.0.1	5/11/2006	Add HL7 Message Listener related pages; Add User Profile page; Updated Search, Tools and Image Thumbnails pages
16.	4.0.2	7/10/2006	Add <a href="#">Unread Studies</a> link to the Main Menu; Add <b>Upload Directory</b> settings to the System Configuration page
17.	4.1.3	11/20/2006	Add <a href="#">Upload Dicom Image</a> to the <b>Tools</b> page; Add <a href="#">Auto-Scan</a> parameters and Thumbnail/Full-Size Images Directories to the Configuration page; Add Preferred Transfer Syntax to the AE Configuration page
18.	4.1.4	1/29/2007	Add Support for Group Users; Add <a href="#">Database Integrity Check</a> to the <b>Tools</b> page

19.	5.1.1	4/12/2007	Added support for Mac OS X
20.	5.1.2	7/15/2007	Added section about Post-Receive Image Compression; Added <u>Import Worklist</u> to the <b>Tools</b> page
21.	5.1.3	10/18/2007	Added Institution Name (0008,0080) to the supported Data Element Coercion table; Added support for Automatic Purging By Study Date and Date When Study Is Received; Added <u>Live Monitor</u> and <u>Patient Reconciliation</u> pages to the <b>Tools</b> menu; Added support for Long-Term Archive Directory and Automatic Aging from Short-Term to Long-Term Archive Directories; Added Dicom Command Filtering for more granulated AE-level access control
22.	5.1.4	01/28/2008	Added more Automatic Routing keys: <b>Study Description (0008,1030)</b> , and <b>Series Description (0008,103E)</b> ; Added <u>Enter New Worklist</u> page for manually entering Modality Worklist data; Added <b>Automatic Worklist Scan</b> option to the System Configuration menu
23.	6.1.1	04/23/2008	Added Immediate <b>[From, To]</b> Schedule option for Automatic Routing; Support multiple email addresses for registered users; Added a <b>&lt;Email JPG Image&gt;</b> button to the full-size image page to send converted JPG/GIF images via email
24.	6.1.2	07/10/2008	Added <b>Automatic Purging By Dicom Data Element Filter</b> ; Added checkboxes for enabling/disabling the daily, weekly or monthly statistics report and the system journal report emails sent to the Administrator's email address; Added more Automatic Routing keys: <b>Modality (0008,0060)</b> , and <b>Modalities In Study (0008,0061)</b>
25.	6.1.3	12/18/2008	Added <b>Study Reconciliation</b> option to the <u>Configuration</u> page; Added detailed examples for <b>Data Element Coercion</b> rules; Added <b>Monitor</b> and <b>Mark Study</b> privileges configurable for individual users and groups; Changed the Post-Receive Image feature to be configurable for each source AE
26.	6.2.1	06/28/2009	Added <b>Compression Ratio</b> and <b>Image Quality</b> settings for JPEG lossy mode compression transfer syntaxes during Post-Receive Image Compression; Added command-level access control for Dicom Modality Worklist (DMWL) querying client applications; Added references to Oracle databases; Added <b>Tools-&gt;Anonymization Templates</b> page
27.	6.2.2	12/28/2009	Added <b>Storage Commitment Report SCP</b> option to the <b>Application Entity</b> page; Added Purge By Source AE Title option to <b>Tools-&gt;Automatic Purge Storage Directories</b> page; Added <b>Sending AE Title</b> as a configurable option when defining Automatic Routing rules; Added <b>Preferred Import Removable Media Drive</b> , <b>Preferred Import Destination Folder</b> and <b>Study/Image Notes Sharing</b> settings to the <u>Profile</u> page
28.	6.2.3	03/10/2010	Added <b>Automatic Routing</b> by both Source AE Title and

			Key Attribute by using the logical AND (&&) operator
29.	6.2.4	9/23/2010	Added <b>Web User Assignment</b> by Source AE Title when logged-in as the Administrator; Added notes about <b>Forwarding N Latest Studies to Destination AE</b> option for the Automatic Routing section; Added non-default character set settings in the <b>Configuration</b> page
30.	6.3.1	4/26/2011	Added <b>Transcription Template</b> (Microsoft Word) in the <b>Tools</b> menu for Windows platforms
31.	6.3.2	9/26/2011	Added optional <b>User Access Filters</b> based on data elements from received Dicom studies; Added support for <b>Preferred Dicom Transfer Syntax</b> for receiving images from a Source AE; Added <b>Advanced Logical Expressions</b> for Automatic Dicom Image Routing
32.	6.3.3	1/28/2012	Added support for configurable <b>Retry Interval</b> for Automatic Routing Rules; Added <b>System Administration</b> privilege to individual or group users for sharing the workload as well as the privilege of the System Administrator; Added configurable number of records displayed in multi-page web user interface pages that can be customized in each web user <u>Profile</u>
33.	6.3.4	4/16/2012	Added support for Web Access to DICOM Persistent Objects ( <b>WADO</b> )
34.	6.3.5	8/28/2012	Added <b>Change Storage</b> privilege for moving selected Dicom studies to a user-specified storage location
35.	6.3.6	1/8/2013	Added configuration for embedding website URL in statistics report emails in the <b>Configuration</b> page
36.	6.3.7	4/28/2013	Added option for sending HL7 ORU message to defined HL7 applications with the URL link to access newly arrived Dicom studies upon receipt
37.	6.3.8	9/28/2013	Added <b>Restart Service</b> page in the <b>Tools</b> menu
38.	6.4.1	1/28/2014	Added Statistics Report by each Source AE defined in the <b>Dicom AE</b> page; Added <b>AE Group Settings</b> in the <b>Dicom AE</b> page
39.	6.4.2	29/05/2014	Added support for <b>Priority Control</b> in Automatic Routing Rules. Added support for automatic restart of all failed forwarding jobs during Dicom Server startup. Added "Sign up now" button in the Login page. Added <b>Search Registered User</b> page in the <b>Search</b> menu. Added support for Multiple User Access Filters that can be defined for each Dicom key attribute. Added support for <b>Dicom X-Ray Radiation Dose Structured Report (SR)</b> storage SOP class (UID 1.2.840.10008.5.1.4.1.1.88.67)
40.	6.4.3	28/09/2014	Added support for <b>Automatic Routing Schedule by a Delayed [From, To] Time Window</b> for PacsOne Server. Added support for Windows 64-bit versions of the ImageMagick PHP extension DLL for PHP 5.4 ( <b>php5.4_imagick.dll</b> ). Added Date-based display filters to the <b>Tools→Check Duplicate Patient ID</b> page. Added support for <b>List Of UID</b> matching method for Dicom

			Query/Retrieve service SOP classes. Added <b>Source AE</b> information in the <b>Tools-&gt;Statistics Report</b> and <b>Daily/Weekly/Monthly Statistics Report</b> emails. Added support for <b>Parallel Dicom Retrieve</b> operations during the Automatic Synchronization with a remote AE. Fixed a bug displaying the patient information when user clicks on the <b>Study Notes and Attachments</b> icon in the study list pages.
41.	6.4.4	28/01/2015	Added support for PHP 5.6. Added Password Complexity requirements for registered web users. Added support for the following Dicom Image Storage SOP classes. Dicom Color Softcopy Presentation State Image Storage SOP class (UID <b>1.2.840.10008.5.1.4.1.1.11.2</b> ). Dicom VL Whole Slide Microscopy Image Storage SOP class (UID <b>1.2.840.10008.5.1.4.1.1.77.1.6</b> ). Dicom Breast Tomosynthesis Image Storage SOP class (UID <b>1.2.840.10008.5.1.4.1.1.13.1.3</b> ). Added support for the <b>Data Element Coercion</b> rule syntax.
42.	6.4.5	01/05/2015	Added <b>Search Dicom AE</b> page in the <b>Search</b> menu. Added support for the <b>Requested Procedure Step Description</b> field in the HL7 ORM Message to Dicom Modality Worklist (DMWL) record mapping table. Update to the latest version ( <b>6.1.5</b> ) of the MySQL Connector/C libraries.
43.	6.4.6	28/09/2015	Added <b>Compress Entire Database</b> page to the <b>Tools</b> menu to compress all images stored in the database via one of the Dicom lossless compression transfer syntaxes. Added <b>Institution Name</b> and <b>Reviewing Web User</b> filters for the <b>Tools-&gt;Statistics Report</b> page. Added option to bypass user authentication for received Dicom study access URL in the HL7 ORU Report messages sent to RIS/HIS systems. Added <b>Preferred Dicom Transfer Syntax</b> configuration for Automatic Routing Rules ( <b>Auto Route</b> ) page. Added Access Control for the Dicom <b>C-GET</b> command for application entities (AEs) configured in the <b>Dicom AE</b> page.
44.	6.5.1	29/01/2016	Added support for <b>CornerStone</b> which is a HTML5/JavaScript based Dicom image viewer
45.	6.5.2	18/05/2016	Added Switch to CornerStone (instead of the AiViewer) as the default browser-based Dicom image viewer. Added Save User Authentication information for the CornerStone Viewer so that the logged-in web users do not have to enter their username/password information again when loading Dicom images into the CornerStone Viewer. Added support for <b>SYSTEMD Service</b> configuration of PacsOne Server for all Linux builds (32-bit and 64-bit)

Table 1 Revisions

---

## **Platforms**

The following platforms are currently supported:

- Windows NT 4.0 Workstation or Server
- Windows 2000 Workstation or Server
- Windows XP
- Windows 2003/2008 Server
- Windows Vista/Windows 7
- Linux (kernel version 2.6 or higher)
- Mac OS X (Release 10.4 or later) for Intel/AMD x86 or x86\_64 processors

---

## Installation

MedDream PACS software can be downloaded from the following URL:

<http://softneta.com/files/meddreampacs/premium/160714/MedDreamPACS-Premium-6.5.2.0-160714.exe>

Refer to the document MedDream PACS Installation Guide for detailed instructions about how to install/upgrade and set up MedDream PACS software.

---

## Managing MedDream PACS User Accounts

After MedDream PACS software has been installed successfully for the first time, there are only two (2) default user accounts created for MedDream PACS:

- The super-user ('`root`' for MySQL or '`SYSTEM`' for Oracle databases), which is the Administrator account required to administrate user accounts and set up privilege levels for all users.
- The `built-in` system user account which you have created during MedDream PACS installation. This account is strictly for MedDream PACS internal use, and it is not recommended to use this account to access the MedDream PACS web user interface since it does not have any associated privilege levels.

### Privacy Attributes

In order to be more compliant with Health Insurance Portability and Accountability Act (HIPAA), all patients and studies stored in the MedDream PACS database have one of the two (2) privacy attributes below:

- Public: If a patient's privacy attribute is `Public`, then all studies of this patient and all images within the studies of this patient can be accessed by any MedDream PACS user account, without any user privilege requirements. If a study's privacy attribute is `Public`, then all subsequent series of this study and all images within the series of this study can be accessed by any MedDream PACS user account, without any user privilege requirements.
- Private (Default): If a patient's privacy attribute is `Private`, then all studies of this patient and all images within the studies of this patient can be accessed by only those MedDream PACS user account (s) with the '`view`' privilege, or those user accounts whose `Last Name` and `First Name` stored in the user profile match with either the `Referring Physician Name` or the `Reading Physician Name`, or those group users whose `Group Description` matches with the `Institution Name` of this patient.
- MedDream PACS users without the '`view`' privilege will not be able to access a `Private` patient or any study or images of the `Private` patient, unless the user's `Last Name` and `First Name` stored in the user profile match with either the `Referring Physician Name` or `Reading Physician Name`, or the user belongs to a `User Group` whose `Group Description` matches with the `Institution Name` of the patient.
- If a study's privacy attribute is `Private`, then all subsequent series of this study and all images within the series of this study can be accessed by only the MedDream PACS user account (s) with the '`view`' privilege, or those user accounts whose `Last Name` and `First Name` stored in the user profile match with either the `Referring Physician Name` or the `Reading Physician Name`, or those `Group Users` whose `Group Description` matches with the `Institution Name` of this patient
- MedDream PACS users without the '`view`' privilege will not be able to access this `Private` study or any series or images of this study, unless the user's `Last Name` and `First Name` stored in the user profile match with either the `Referring Physician Name` or `Reading Physician Name`, or the user belongs to a `User Group` whose `Group Description` matches with the `Institution Name` of this study.
- All patients and studies are stored as `Private` when they are received by MedDream PACS. Only MedDream PACS users with '`modify`' privilege can change the privacy attribute of a patient or study from `Private` to `Public` and vice versa.
- Changing a patient from `Private` to `Public` will implicitly change all studies of the patient to `Public`, regardless of their previous settings.
- Changing a patient from `Public` to `Private` will implicitly change all studies of the patient to `Private`, regardless of their previous settings.

- Changing a study from `Private` to `Public` does not affect the privacy setting of the patient who this study belongs to, except when this study is the only study of the patient. The patient will also be changed from `Private` to `Public` if and only if the study being changed is the only study of that patient.
- Changing a study from `Public` to `Private` does not affect the privacy setting of the patient who this study belongs to, except when this study is the only study of the patient. The patient will also be changed from `Public` to `Private` if and only if the study being changed is the only study of that patient.
- `User Access Filters` – The Administrator can define optional **User Access Filters** to allow this user access to the specific patient or study with the matching Dicom data element filter values. The following list of Dicom Data Elements is supported as the filtering attribute:
  - `Source AE Title`
  - `Referring Physician's Name`
  - `Reading Physician's Name`
  - `Institution Name`

If multiple filters are defined, then the logical **AND (&&)** operator will be applied for all defined filters.

## Creating New User Accounts

Only the Administrator/Super-user ('`root`' for MySQL or '`SYSTEM`' for Oracle databases) can create new user accounts, after logging into MedDream PACS by accessing the following URL:

`http://{HOSTNAME}/MedDream PACS/home.php`

Where: {HOSTNAME} is the name of the machine where MedDream PACS is installed, e.g. `localhost`. After logging into MedDream PACS successfully, the Administrator ('`root`' for MySQL or '`SYSTEM`' for Oracle databases) can click on the '`User Administration`' link from the menu bar to enter the User Administration page as illustrated below:

Privacy	Patient ID	Patient Name	Patient's Sex	Date of Birth	Age	Institution Name	Study ID	Study Date	Study Time	Received On	Accession Number	Referring Physician's Name	Description	Reading Physician's Name	Read By	Reading Physician's Name	Status	Total Number of Instances
Private Change to Public	0	Anonymized	M	N/A	29	N/A	1	2016-02-18	09:17:00	2016-05-26 13:11:28	N/A	N/A	UPPER GI / SIM BOWEL WITH AIR	N/A	_GROUP administrator	N/A	SENDTOPACS - SENDTOPACS	1
Private Change to Public	N/A	Ptose Name	O	N/A	25	N/A	Study Details	2013-06-05	16:52:15	2016-05-26 13:11:27	N/A	N/A	US ABDOMEN LTD	N/A	_GROUP administrator	N/A	SENDTOPACS - SENDTOPACS	1

Figure 1 User Accounts Administration

Clicking on the '`Add`' button will display the "Add New User" page as illustrated below:

MedDream PACS | Home | Logout | @ | Admin

User Administration | Configuration | Email | Journal | Home | Street Orders | Device | Search | Device AC | Run Profile | Job Status | Modality Worklist | Tools | Profile | Help

Software

Add New Admin User

Enter Username:	This is the username to login to the database	<input type="text"/>
Enter Password:	Password for the database username above	<input type="password"/>
Enter User's First Name:	Firstname of the user (up to 25 characters)	<input type="text"/>
Enter User's Last Name:	Lastname of the user (up to 25 characters)	<input type="text"/>
Enter User's Middle Name:	Middlename of the user (up to 25 characters)	<input type="text"/>
Enter User's Email Address:	Email address of the User (up to 54 characters)	<input type="text"/>
Email Notification:	Send Email Notification When New Study with This User Being the Referring Physician has Arrived	<input checked="" type="checkbox"/> No <input type="checkbox"/> Yes
Select View privilege:	Privilege to view private patients/studies stored in MedDreamPACS-Premium database	<input type="checkbox"/> Enable <input checked="" type="checkbox"/> Disable
Select Modify privilege:	Privilege to modify MedDreamPACS-Premium database tables	<input type="checkbox"/> Enable <input checked="" type="checkbox"/> Disable
Select Forward privilege:	Privilege to forward images stored in MedDreamPACS-Premium database to remote AEs	<input checked="" type="checkbox"/> Enable <input type="checkbox"/> Disable
Select Query privilege:	Privilege to query remote Query/Retrieve SCP applications	<input checked="" type="checkbox"/> Enable <input type="checkbox"/> Disable
Select Move privilege:	Privilege to move images stored in remote Query/Retrieve SCP applications	<input checked="" type="checkbox"/> Enable <input type="checkbox"/> Disable
Select Download privilege:	Privilege to download images from web browser via Microsoft Internet Explorer	<input checked="" type="checkbox"/> Enable <input type="checkbox"/> Disable
Select Print privilege:	Privilege to print images from web browser via Microsoft Internet Explorer	<input checked="" type="checkbox"/> Enable <input type="checkbox"/> Disable
Select Export privilege:	Privilege to Export studies for Dicom-compliance media interchange	<input checked="" type="checkbox"/> Enable <input type="checkbox"/> Disable
Select Import privilege:	Privilege to Import images from Dicom formatted media or storage	<input checked="" type="checkbox"/> Enable <input type="checkbox"/> Disable
Select Upload privilege:	Privilege to upload files such as notes, Word/DOC documents, audio/video clips, etc.	<input type="checkbox"/> Enable <input checked="" type="checkbox"/> Disable

Figure 2 Creating New User Account

For each user, there are 12 privileges that can be administrated separately by the super-user/Administrator ('root' for MySQL or 'SYSTEM' for Oracle databases):

Privilege	Description	Default
View	Required to view private patients/studies	Disabled
Modify	Required to change database attributes	Disabled
Forward	Required to forward images stored in MedDream PACS to a remote SCP	Enabled
Query	Required to query remote Query/Retrieve SCP application entities	Enabled
Move	Required to move images on remote Query/Retrieve SCP application entities	Enabled
Download	Required to download MedDream PACS images from a web browser	Enabled
Print	Required to print images to Dicom printers	Enabled
Export	Required to export images stored in local MedDream PACS database to Dicom Standard Part 10 formatted directory and files with DICOMDIR directory information	Enabled
Import	Required to import external Dicom formatted directory and/or raw image files into MedDream PACS database	Enabled
Upload	Required to upload text files, PDF/Word documents, audio/video clips, etc. into MedDream PACS database	Disabled
Monitor	Required to access system monitoring activities such as system logs, live monitors, etc.	Disabled

Mark Study	Required to mark a study as either Read or Un-read	Disabled
System Administration	Required to access system-level configurations such as Email Server, System Configuration, Journal, or System-level Job Status, etc.	Disabled
Change Storage	Required to move selected Dicom studies to a user-specified storage location	Disabled

Table 2 MedDream PACS User Privileges

NOTE: The Super-user/Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases) has all of the above privileges.

With the above privilege levels, there are three (3) categories of users that can be defined for MedDream PACS Premium Edition:

Category	Description
Administrator	This is the pre-defined user account ' <b>root</b> ' for MySQL or ' <b>SYSTEM</b> ' for Oracle databases. There is only one (1) such account and it is required to perform all user administration tasks.
System Administrators	These are the user accounts with the ' <b>System Administration</b> ' privilege Enabled by the Administrator. These users can access system-level configuration information such as the Email Server, System Configuration, Journal, or System-level Job Status pages, etc.
Power Users	These are the user accounts with the ' <b>Modify</b> ' and ' <b>View</b> ' privileges Enabled by the Administrator. These users can access all <code>Public</code> and <code>Private</code> patients/studies in the database, and they can also modify and delete existing database records.
Regular Users	These accounts are usually created for the referring physicians or reading physicians. They do not have the ' <b>View</b> ' privilege and can only access the <code>Public</code> patients/studies, or the <code>Private</code> patients/studies whose <code>Referring/Reading Physician Name</code> matches with the <code>Last Name</code> and <code>First Name</code> of the user profile.

Table 3 MedDream PACS User Categories

## Creating Group User Accounts

Clicking on the ‘Add User Group’ button will display the “Add New User Group” page as illustrated below:

Privilege	Description	Enable/Disable
Special View privilege	Privilege to view private patient/studies stored in MedDreamPACS Premium database.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Query privilege	Privilege to modify MedDreamPACS Premium database tables.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Forward privilege	Privilege to forward images stored in MedDreamPACS Premium database to remote sites.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Query privilege	Privilege to query remote SOAP/HL7/SCP applications.	<input type="radio"/> Enable <input type="radio"/> Disable
Special View privilege	Privilege to view images stored in remote Query/HL7/SCP applications.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Download privilege	Privilege to download images from web browsers via Microsoft Internet Explorer.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Print privilege	Privilege to print images from web browsers via Microsoft Internet Explorer.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Export privilege	Privilege to export studies for DICOM compatible media interchange.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Import privilege	Privilege to import studies from DICOM compatible media interchange.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Mailbox privilege	Privilege to upload files such as notes, Word/Excel documents, attachments, etc. etc.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Backup privilege	Privilege to assist system monitoring activities such as system logs, low resources, etc.	<input type="radio"/> Enable <input type="radio"/> Disable
Special Share Library privilege	Privilege to make a study available on the web.	<input type="radio"/> Enable <input type="radio"/> Disable

Figure 3 Creating Group User Accounts

A Group User account has almost the same attributes as a normal user account, e.g., username/password, email address, privileges, etc., except that the `Group Description` of a Group User account is used by MedDream PACS to match against the `Institution Name` of a private patient/study, when determining if the Group User can access that private patient/study. In addition to all the privileges of a regular user account, a Group User has the following configurable options that can be administered only for Group Users:

Option	Description	Default
Group Share	If this privilege is enabled, MedDream PACS will check all users of the group and see if any of them has a matching Referring, Reading or Requesting Physician’s Name of a private study, to determine whether users of the group can access that private study. For example, if a user of this group has a matching last name/first name with either the Referring, Reading or Requesting Physician’s Name of a private study, and this privilege is enabled for the Group of that user, then all other users of this group can access the same private study.	Disabled
Sub-String Group Matching	If this option is enabled, then instead of using <b>Exact-Matching</b> method when checking if this group has access to a private patient, MedDream PACS will check whether the <b>Group Description</b> of this group is a sub-string of the <b>Institution Name</b> of that patient.	Disabled

Table 4 Options Specific for Group Users

## Deleting Existing User Accounts

Only the Administrator/Super-user (‘root’ for MySQL or ‘SYSTEM’ for Oracle databases) can delete existing MedDream PACS user accounts from the `User Administration` page, by clicking the individual checkbox before

the MedDream PACS username (or click the 'check All' button to delete all existing users) followed by the 'Delete' button.

## Modifying Existing User Accounts

Only the Administrator/Super-user ('root' for MySQL or 'SYSTEM' for Oracle databases) can modify existing MedDream PACS user accounts from the User Administration page, by clicking the 'Edit' link (marked in red Figure 4) for the particular user account that needs to be modified.

The screenshot shows the 'User Administration' page in MedDream PACS. At the top, there is a navigation bar with links like 'User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help'. Below this, there is a section for 'Server Instance demo' with a sub-header 'There is 0 user account in PACS database.' and an 'Add' button. The main section is titled 'There is 1 user group in PACS database.' and contains a table with columns for 'Username', 'Group Name', 'Email', and various privileges. The table has one row for 'PACSOne' with a checked checkbox and 'PACSOne' as the group name. The 'Edit' button in the last column of this row is highlighted with a red box. Below the table are buttons for 'Check All', 'Delete User Group', and 'Add User Group'. At the bottom, there is a section for 'There is 0 user sign-up request.' with a table and buttons for 'Check All', 'Approve', 'Reject', and 'Delete'.

Username	Group Name	Email	View Private Data	Modify	Forward	Query	Move	Download	Print	Export	Import	Upload	Monitor	Mark Study	System Administration	Change Storage Location	Group Share	Sub-String Group Matching	Edit
<input checked="" type="checkbox"/>	PACSOne	PACSOne	✓	✓	✓	✓	✓	✓	✓	✓	✓	✗	✗	✗	✗	✗	✗	✗	Edit

Figure 4 Modifying Existing User Account

The user's password, first name, last name, middle name can be modified, and all of the six (6) privileges can be independently Enabled or Disabled for this user account.

---

## System Configuration

The Administrator ('`root`' for MySQL or '`SYSTEM`' for Oracle databases) of MedDream PACS can configure the following system parameters by clicking on the [Configuration](#) link from the **Main Menu** bar:

- `Default Short-term Archive Directory` – This is the directory where the received images will be stored if there is no specific short-term archive directory defined for the source AE.
- `Default Long-Term Archive Directory` – This is the directory where the received images will be stored if there is no specific long-term archive directory defined for the source AE.
- `Default Archive Directory Format` – This parameter controls the directory hierarchy under the designated archive directory. There are three (3) options:
  - `Flat` - Received images are stored under `%Assigned Directory%/YYYY-MM-DD-WEEKDAY/` sub-folders
  - `Hierarchical` - Received images are stored under `%Assigned Directory%/YYYY/MM/DD/` sub-folders
  - `Study Instance UID` - Received images are stored under `%Assigned Directory%/StudyInstanceUID/` sub-folders, where `StudyInstanceUID` is the Study Instance UID of the received Dicom studies
- `Automatically Age From Default Short-Term Archive Directory To Default Long-Term Archive Directory` – If this option is enabled, MedDream PACS will automatically move images stored under the default short-term archive directory that were received more than `N` days ago, to the default long-term directory specified by the Administrator ('`root`' for MySQL or '`SYSTEM`' for Oracle databases).
- `Date and Time Schedule for Automatic Aging from Short-term to Long-term Archive Directory` – This parameter controls the schedule when MedDream PACS will perform the automatic aging to move images from short-term to long-term directories. The default schedule is every Sunday morning at 01:00 a.m. local time.
- `Automatically Logout Browser Sessions After This Idle Period` – This parameter controls the timeout/idle period (in minutes) for automatic logging out client browsers. The default value is 10 minutes
- `Automatically Expire User Passwords After` – This parameter controls the time period for automatic user password expiration, users need to select a new password when their passwords expire. The default value is 60 days.
- `Maximum Upload File Size` – This parameter controls the maximum file size limit when users upload files. The default value is 2 MB. The smaller value of this parameter and the `upload_max_filesize` variable in your '`PHP.INI`' file controls the maximum file size limit when users upload files.
- `Upload Directory for Storing User-uploaded Attachments and Dicom Images` – This is the local directory used to store user-uploaded attachments and Dicom Part-10 formatted raw images. The default value is the '`upload`' sub-folder where MedDream PACS is installed.
- `Upload Attachment` – Whether MedDream PACS should store uploaded attachment into the database table directly, or store them as regular files under the above '`Upload Directory`'. The default is to store attachment into the database table directly.
- `Directory for Storing Thumbnail Converted JPG/GIF Images` – This is the directory used to store the cached thumbnail .jpg/.gif images displayed to the browsers. The default is to store the .jpg/.gif images under the "`php/thumbnails`" sub-folder where MedDream PACS is installed.
- `Directory for Storing Converted JPG/GIF Images` – This is the directory used to store the cached full-size .jpg/.gif images displayed to the browsers. The default is to store the .jpg/.gif images under the "`php/images`" sub-folder where MedDream PACS is installed.

- 
- **Auto-Scan Directory for Importing Dicom images**– The Administrator (`'root'` for MySQL or `'SYSTEM'` for Oracle databases) can enable or disable this feature, and if enabled, MedDream PACS will automatically scan the configured **Source Directory**, using the configured scan interval:

- **Auto-Scan Source Directory** – If enabled, MedDream PACS will automatically scan this local directory for any Dicom Part-10 formatted images with the `"*.dcm"` filename extension. If the image are indeed Dicom Part-10 formatted but the image files do not end with the `"*.dcm"` filename extension, you can force MedDream PACS to scan all files under this source directory, by adding the following Registry value (for Windows users):

```
HKEY_LOCAL_MACHINE\Software\Softneta\MedDream PACS\${AeTitle}\AutoScanAnyFile
```

And set the DWORD value to 1.

For Linux/Mac OS X users, the same configuration can be set by adding the following line to the `"${AeTitle}.ini"` file under the directory where MedDream PACS is installed:

```
AutoScanAnyFile = 1
```

- **Auto Scan Destination Folder** – If MedDream PACS has found and scanned any Dicom Part-10 formatted image in the **Source Directory**, it will move the image to this **Destination Folder** and parse it into the MedDream PACS database
- **Scan Interval** – Time interval (in seconds) for the period scan of the above **Source Directory**. The default value is 60 seconds and the Administrator (`'root'` for MySQL or `'SYSTEM'` for Oracle databases) can set it to any value larger than 60 seconds

This Auto-Scan feature is by default **Disabled** and can only be enabled by the Administrator (`'root'` for MySQL or `'SYSTEM'` for Oracle databases).

- **Administrator's Email Address** – This is the email address where the automatically-generated emails (e.g., [Statistics Reports](#), [System Journal Logs](#), etc.) will be delivered to. Multiple email addresses can be entered by using the coma (',') as the separator in between the addresses.
- **Path to PHP Runtime Executable** – Full path to the PHP runtime executable program (`'php.exe'`). Default is `"C:\php\php.exe"` for Windows platforms, or `"/usr/local/bin/php"` for Linux/MacOS. This is required because MedDream PACS uses PHP internally to send outgoing emails.
- **Email Notify Users About Failed Jobs** – If enabled, MedDream PACS will send email notifications to registered user's email address (if defined) about any failed job submitted by that user.

## Current System Configurations:

Default Short-Term Archive Directory:	<input type="text" value="D:/MedDreamPACS-Premium/DICOM/"/>
Default Archive Directory Format:	<input checked="" type="radio"/> Flat (Received images are stored under %Assigned Directory%/YYYY-MM-DD-WEEKDAY/ sub-folders) <input type="radio"/> Hierarchical (Received images are stored under %Assigned Directory%/YYYY/MM/DD/ sub-folders) <input type="radio"/> Study Instance UID (Received images are stored under %Assigned Directory%/StudyInstanceUid/ sub-folders)
Default Long-Term Archive Directory:	<input type="text"/>
Automatically Age From Default Short-Term Archive Directory To Default Long-Term Archive Directory:	<input checked="" type="radio"/> Disabled <input type="radio"/> Age Images Received More Than <input type="text" value="0"/> Days Ago
Date and Time Schedule for Automatic Aging from Short-term to Long-term Archive Directory:	Run Automatic Aging Weekly On Every <input type="text" value="Sunday"/> At: <input type="text" value="12:00 AM"/>
Automatically Logout Browser Sessions After This Idle Period:	<input type="text" value="10"/> Minutes
Automatically Expire User Passwords After:	<input type="text" value="60"/> Days
Maximum Upload File Size:	<input type="text" value="2"/> MBytes
Bypass Displaying of the Series Level and Display All Images of a Study Directly, Without Displaying Series of That Study First:	<input type="radio"/> Yes <input checked="" type="radio"/> No
Upload Directory for Storing User-uploaded Attachments and Dicom Images:	<input type="text"/>
Upload Attachments:	<input checked="" type="radio"/> Store uploaded attachment into database table directly <input type="radio"/> Store uploaded attachment under the above Upload Directory.

Figure 5 System Configuration Page

- Automatic Patient Reconciliation** – If enabled, MedDream PACS will use the patient demographics information (Patient ID, Patient Name and Date of Birth) from the Dicom Modality Worklist (DMWL) data or the HL7 Patient Order (ORM) messages to match with the same information contained in the received Dicom studies, and will automatically correct the Patient Name if there is any discrepancy found in the received Dicom studies. For example, if the scheduled DMWL/HL7 ORM data has a patient with the Patient ID of “12345”, Patient Name of “Doe^John” and DOB of “2007-10-18”, then a Dicom study is received with the same Patient ID and DOB, but different Patient Name of “Doe^Johnny”. In this case, if the **Automatic Patient Reconciliation** feature is enabled, MedDream PACS will automatically correct the Patient Name in this received Dicom study to “Doe^John” to match with the Patient Name in the DMWL/HL7 ORM data, and log this event to the **Patient Reconciliation** table described in [Section 0](#).
- Automatic Study Reconciliation** – If enabled, MedDream PACS will use the study related information (Referring Physician’s Name, Requesting Physician’s Name) from the Dicom Modality Worklist (DMWL) data to match with the same information contained in the received Dicom studies, and will automatically correct the Referring Physician’s Name and/or Requesting Physician’s Name if there is any discrepancy found in the received Dicom studies. For example, if the DMWL data has a procedure scheduled with the Referring Physician’s Name of “Doe^John”, then a Dicom study is received with the same Study Instance UID but different Referring Physician’s Name of “Doe^Johnny”. In this case, if the **Automatic Study Reconciliation** feature is enabled, MedDream PACS will automatically correct the Referring Physician’s Name in this received Dicom study to “Doe^John” to match with the Referring Physician’s Name from the DMWL data
- Auto-Scan Directory for Worklist Data** – The Administrator (‘root’ for MySQL or ‘SYSTEM’ for Oracle databases) can enable or disable this feature, and if enabled, MedDream PACS will automatically scan the configured **Source Directory**, using the configured scan interval:
  - Source Directory** – If enabled, MedDream PACS will automatically scan this local directory for any text files that may contain the Dicom Modality Worklist (DMWL) data.
  - Scan Interval** – Time interval (in seconds) for the period scan of the above **Source Directory**. The default value is 60 seconds and the Administrator (‘root’ for MySQL or ‘SYSTEM’ for Oracle databases) can set it to any value larger than 60 seconds

This Auto-Scan Worklist feature is by default **disabled** and can only be enabled by the Administrator (‘root’ for MySQL or ‘SYSTEM’ for Oracle databases).

- 
- **Enable Statistics Report Emails** – The Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases) can enable or disable the checkboxes for the daily, weekly or monthly statistics report emails, as well as the monthly journal report emails, that are sent to the Administrator's email address.
  - **Enable Automatic Conversion of Received Dicom Images into Thumbnail/Full-size JPG/GIF images** – If enabled by the Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases), MedDream PACS will automatically convert received Dicom images into the thumbnail/full-size JPG/GIF images upon reception, so that the converted JPG/GIF images can be loaded much faster by the web browsers when comparing to the case where the JPG/GIF images must be converted on-demand.
  - **Enable Display of Veterinary Specific Information** – If enabled by the Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases), MedDream PACS will display database columns or information that are specific for veterinary systems, for example, patient species, patient breed, owner, etc.
  - **Select Specific Character Set** – Instead of the Dicom default character set (ISO IR-6), the Administrator can select from the following non-default character sets:
    - Simplified Chinese - ISO IR-192/GB18030
    - Korean - ISO IR-149
    - Japanese JIS X 0201 – ISO IR-13
    - Japanese JIS X 0208 – ISO IR-87
    - Japanese JIS X 0212 – ISO IR-159
    - Unicode - ISO IR-192
  - **Web Access to DICOM Persistent Objects (WADO) Security Model** – MedDream PACS requires authentication (username/password) for Web Access to DICOM Persistent Objects (WADO). There are 2 authentication methods supported:
    - Use Username/Password from HTTP GET/POST Request or Basic Authentication
    - Use Pre-Configured Username/PasswordEither method requires the specified username/password to be valid, and should be pre-configured by the Administrator from the "**User Administration**" page described in [Section 0](#).
  - **Website URL to embed in statistics report emails for external access** – This configuration is used to embed website URL in the statistics report emails sent from MedDream PACS, so that users can simply click on the embedded URL link in the emails to launch a web browser to access the URL-linked Dicom studies. The website URL should be the external domain name (DNS) or IP address of the web server where MedDream PACS database is hosted, e.g., <http://127.0.0.1/Pacs/>, etc.

---

## SMTP Server Configuration

The Administrator ('root' for MySQL or 'SYSTEM' for Oracle databases) of MedDream PACS can configure a SMTP server for sending outgoing emails, by clicking on the [Email](#) link from the Main Menu, and enter the following information:

- SMTP Server Hostname or IP Address – This is the hostname or IP address of the SMTP server, which can be either the same server (localhost) or a remote host
- Port Number – The TCP port number the SMTP server listens to. Default is 25
- Description – Text description of this SMTP server
- From: Email Address – This is the email address used in the **From:** field in outgoing email messages
- Authentication Type – SMTP authentication type. Can be set to one of the following:
  - None – No other configuration is required
  - LOGIN, CRAM-MD5, or PLAIN – A valid username/password pair is required
  - NTLM – A valid username/password pair, and the hostname of the NTLM Workstation are required

The screenshot shows the MedDream PACS user interface for configuring an SMTP server. The page has a dark blue header with navigation links: MedDream PACS | About | Logout root @ demo | User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help. The Softmeta logo is in the top right corner. The main content area contains a form with the following fields:

Enter SMTP Server Hostname or IP Address:	<input type="text"/>
Enter Port Number:	<input type="text" value="25"/>
Enter Description of SMTP Server:	<input type="text"/>
Enter FROM Email Address: (This address will be used in the FROM: field in all emails sent using this SMTP server)	<input type="text"/>
Enter Authentication Type:	<p><input checked="" type="radio"/> None</p> <p><input type="radio"/> Mechanism: <input type="text" value="LOGIN"/> <input type="button" value="v"/></p> <p>Username: <input type="text"/> Password: <input type="text"/></p> <p><input type="radio"/> NTLM Workstation: <input type="text"/></p>

Below the form is an  button.

Figure 6 Configuring SMTP Server

---

## System Journal Log

To support HIPAA Auditing requirements, MedDream PACS automatically logs all user activities into the **System Journal Log** table, and only the Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases) can access this table by clicking on the **Journal1** link from the Main Menu. The following information will be displayed from the **System Journal Log**:

- **When** – The date and time when the event took place
- **Username** – The username for which the event was logged
- **Operation** – The operation this user performed for which the event was logged
- **Level** – The subject level of this event, e.g., Patient, Study, Series, Image, etc.
- **UID** – The unique ID identifying this event, e.g., Patient ID, Study/Series/Instance UID, etc.
- **Details** – The details of this event

MedDream PACS | About | Logout root @ demo

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Softmeta

Today's Activities | Yesterday's Activities | This Week's Activities | This Month's Activities | Last Month's Activities | All Activities

There are 1 events logged.

Previous Next

Displaying 1-1 of 1 Events:

When	Username	Operation	Level	UID	Details
2016-05-31 15:20:28	root	Add	Group	PACSOne	N/A

Figure 7 System Journal Log

The Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases) can choose from the following time-based views of the events logged in the **System Journal Log**:

- Today's Activities
- Yesterday's Activities
- This Week's Activities
- This Month's Activities
- Last Month's Activities
- All Activities

---

## Automatic Monthly System Journal Log Emails

If a valid SMTP server and the Administrator ('root' for MySQL or 'SYSTEM' for Oracle databases)'s email address have been configured (See [Section 7](#) above), then on the first day of every month, MedDream PACS will automatically send an email with all events in the **System Journal Log** during the previous month to the configured Administrator's email address.

## Automatic Purging Aged System Journal Log

On the first day of every month, MedDream PACS will automatically purge older events logged in the **System Journal Log** that occurred before the first day of the previous month.

To change the purge interval for system journal logs from the default 60 days, users can add or modify the following Registry value:

```
HKEY_LOCAL_MACHINE\Software\Softneta\MedDream PACS\{AETITLE}\JournalPurgeInterval
```

Set or change the DWORD value to the Number of Days in which the older system journal logs will be purged.

## Application Entity Table

Before MedDream PACS can communicate with other DICOM compliant application entities, they need to be configured properly in the `Application Entity` table as described below:

Column	Description	SCU or SCP Role	Default
Title	Application Entity (AE) Title. This is the key of this table.	Both	N/A
Hostname	Hostname of the remote AE. This is used to lookup the IP address of the remote AE if the IP address is not defined.	Both	None
IP Address	IP address of the remote AE.	Both	None
Port	TCP port number of the remote AE.	SCP	None
Database Access	'Enable' or 'Disable' access to MedDream PACS database for this remote application entity. If set to 'Disable', MedDream PACS will reject any association requests with the specified application entity title.	Both	Disabled
Allow Dicom Commands	<p>Enable or Disable the following individual Dicom commands sent from the remote AE:</p> <ul style="list-style-type: none"> <li>◆ C-FIND</li> <li>◆ C-MOVE</li> <li>◆ C-STORE</li> <li>◆ C-FIND</li> <li>◆ Modality Worklist - FIND</li> </ul> <p>Data element or key-based filters can be defined for each of the above enabled commands.</p>	SCU	Allow <b>C-FIND</b> , <b>C-STORE</b> , <b>C-MOVE</b> and <b>Modality Worklist – FIND</b> with no filters
Short-Term Archive Directory	Short-term archive directory path for this AE. This field is required for C-STORE SCU clients. MedDream PACS will store received images under this directory based on the <b>Archive Directory Format</b> for this AE.	SCU	None
Archive Directory Format	Either <b>Flat</b> or <b>Hierarchical</b> format for storing images received from this AE.	SCU	Flat format
Long-Term Archive Directory	Long-term archive directory path for this AE. If this field is defined and <b>Automatic Aging</b> is enabled for this AE, MedDream PACS will automatically age/move images stored in the Short-Term Archive Directory to	SCU	None

	this Long-Term Archive Directory.		
Send Email Notification	Send email notification to the user registered as the Referring Physician when a new Dicom study from this AE is received.	SCU	No
Compress Received Images	Compress images received from this AE via the selected Dicom compression transfer.	SCU	Disabled
Query SCP	Boolean flag indicating whether this remote AE is a DICOM Query/Retrieve SCP or not.	SCP	False
Worklist SCP	Boolean flag indicating whether this remote AE is a DICOM Modality Worklist Management SCP or not.	SCP	False
Print SCP	Boolean flag indicating whether this remote AE is a DICOM Printer or not.	SCP	False
Storage Commitment Report SCP	Boolean flag indicating whether this remote AE is a DICOM Storage Commitment Report SCP or not. If the <b>“Request Storage Commitment Report for Dicom images sent to this SCP”</b> option is enabled for this SCP, MedDream PACS will request for Storage Commitment Report for any image sent to this SCP.	SCP	False
Maximum Outgoing Sessions	The maximum number of simultaneous outgoing connections MedDream PACS will establish with the remote AE.	SCP	10
Preferred Transfer Syntax Tx	Users can define a preferred transfer syntax for this AE, so that MedDream PACS will prefer to use this defined transfer syntax when sending images to this remote AE.	SCP	Use original transfer syntax when image was received
Separate Dicom Presentation Context	If this option is enabled, MedDream PACS will propose a separate Dicom Presentation Context for each supported Transfer Syntax when sending images to this destination AE.	SCP	No
Preferred Transfer Syntax Rx	Users can define a preferred transfer syntax for this Source AE, so that MedDream PACS will prefer to use this defined transfer syntax when receiving images from this Source AE.	SCU	None
Mark Retrieved Studies as Read	Mark studies retrieved to this AE as <b>Read</b> with the AE Title of this AE.	SCP	No
Job Queue Priority	Job queue priority when processing database jobs with this destination AE (default priority is 0 - Normal. Database jobs with higher priority destination AEs will be processed before those jobs with lower priority destination AEs).	SCP	0
Anonymize Received Studies	Anonymized studies received from this AE via the syntax rules in a pre-defined template.	SCU	Disabled
Assign Dicom Studies Received From This AE To Web Users	Assign Dicom studies received from this Source AE to specified web users.	SCU	Disabled

AE Group Settings	Configure one or more individual Source AEs as a group, so that the group AE can be used as the Destination AE for Automatic Routing.	SCP	No
-------------------	---	-----	----

Table 5 Application Entity Table

For security purposes, only those users with 'Modify' privilege can create, modify or delete entries in the Application Entity table. Click on the 'Application Entity' link from the Main Menu bar to view, add, modify or delete entries in the Application Entity table, which is illustrated below:

Figure 8 Adding a New Application Entity

The following attributes are common among all Dicom SCU or SCP applications:

- AE Title – Dicom Application Entity (AE) Title string. Maximum of 16 characters with no white-space characters
- Description – Text description of this Dicom AE
- Hostname – Name of the host where this Dicom AE is located
- IP Address – IP address of the host where this Dicom AE is located

MedDream PACS | Admin | Logout | 08:00:00

User Administration | Configuration | Email | Journal | Home | Internal Studies | Down | Search | Secure AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Current MedDreamACS-Physician Configurations:

- Application Entry Title: **Acad**
- Business: **10004.001**
- TCU Port Number: **999**

There are 1 Application Entities defined.

AE Title	AccessGroup	Host	IP Address	Port Number	Enable Access	Archive Directory	Allow Dicom Command	Maximum Connections	Preferred Transfer Syntax Le	Preferred Transfer Syntax Da	Group	Disk Usage	Verify Connection	Application Type	SQL
<input type="checkbox"/> SENDTOPACS	SENDTOPACS	127.0.0.1	N/A	N/A	<input checked="" type="checkbox"/>	N/A	C-STORE C-FIND C-MOVE C-GET WORKLISTFIND	10	N/A	N/A	0	N/A	N/A	N/A	EDIT

Figure 9 Application Entity Table Page

## SCU Application Entities

In addition to the columns common to the Application Entity table, i.e. AE Title, Hostname, IP Address, the following SCU specific values will be displayed in the Application Entity Table page if the AE is a SCU:

- **Allow Access** – Whether to enable or disable access for this AE
- **Allow Dicom Commands** – Whether to enable or disable Dicom commands (C-STORE, C-FIND, C-MOVE, and Modality Worklist - FIND) sent from this SCU. Additionally, for each enabled command, the following data element or key-based filters can be defined to further match the enabled Dicom command:
  - **Institution Name** – (0008,0080)
  - **Referring Physician's Name** – (0008,0090)
  - **Reading Physician's Name** – (0008,1060)

For each of the above filters, a string pattern (including wild-card characters '\*' and '?') can be specified to match against the received image or Dicom command messages. For example:

- If the Dicom C-FIND command is enabled for a source AE, and a filter for Institution Name is defined with the string pattern of "Springfield General", then MedDream PACS will allow Dicom Queries (C-FIND) from this source AE, but will only return matching results for those patients with the matching Institution Name of "Springfield General".
- If multiple filters are defined for an enabled command, then the filters will be combined with logical OR ('||') operators. For example, if both a filter for Institution Name pattern of "Springfield\*" and a filter for Referring Physician's Name pattern of "Dr. Hibbert" are defined for the Dicom C-STORE command, then MedDream PACS will allow Dicom C-STORE command sent from this source AE, but will only accept images that either pattern match with the Institution Name of "Springfield\*", or the Referring Physician's Name of "Dr. Hibbert".
- For the same filtering key or data element, multiple string patterns can be specified by using the semicolon (;) as the delimiter. For example, for the same Institution Name filter, if the string pattern of "Springfield\* ; Capital City\*" is defined for the Dicom C-STORE command, then MedDream PACS will only accept images that either pattern match with the Institution Name of "Springfield\*", or the Institution Name of "Capital City\*".
- If a Dicom command is enabled for a source AE, but no filter is defined for that command, then MedDream PACS will always accept that Dicom command sent from the source AE without any filtering.
- **Short-Term Archive Dir** – Short-Term Archive directory for this AE if this AE is a C-STORE SCU.
  - On Windows platforms, this directory path can be set to a folder on a local disk, e.g., C:\Images\CT\, or it can be set to a network-shared path in Windows Universal Naming Convention (UNC) format, e.g.,

---

\\Hostname\Dir\SubDir\. NOTE: When using network-shared path as archive directories, users must make sure that the Windows local user account (default is 'SYSTEM') MedDream PACS is using has Full access to the network-shared path

- On Linux platforms, both the local disks and the network attached storage paths are accessed via the standard UNIX "/" path specifications, e.g., /home/images/CT/. NOTE: When using network-attached storage path as archive directories, users must make sure that the user account (default is 'root') MedDream PACS is using has Read/Write privileges to the network-attached storage path
- Archive Directory Format – Users can choose from the following directory layouts:
  - Flat – Received images are stored under current-date based (YYYY-MM-DD-WEEKDAY/) sub-folders under the assigned archive directory. For example, if today is January 15, 2006, then all images received today are stored under \$AssignedDirectory/2006-01-15-SUN/.
  - Hierarchical – Received images are stored under current-date based (YYYY/MM/DD/) sub-folders under the assigned archive directory. For example, if today is January 15, 2006, then all images received today are stored under \$AssignedDirectory/2006/01/15/.
  - Study UID – Received images are stored under the Dicom Study Instance UID sub-folders under the assigned archive directory. For example, if the Study Instance UID of the received Dicom study is "1.2.840.113674.514.212.200", then all images of that study will be stored under \$AssignedDirectory/ 1.2.840.113674.514.212.200/.
- Long-Term Archive Directory – Long-Term Archive directory for this AE. See the **Automatic Aging** option below.
- Automatically Age From Short-Term Archive Directory To Long-Term Archive Directory – If this option is enabled, and the **Long-Term Archive Directory** above is defined, then MedDream PACS will automatically age images stored in the Short-Term Archive Directory to the defined Long-Term Archive Directory, by moving all images stored under the Short-Term Archive Directory that were received prior to the user-defined **Aging Period** (in days) to the defined Long-Term Archive Directory.
- Date/Time Schedule for Automatic Aging – Weekly date/time schedule to perform the Automatic Aging from short-term to long-term archive directories. For example, every Sunday at 12:00 am, etc.
- Directory Usage – Current disk space usage of the Archive Directory if this AE is a C-STORE SCU
- Send Email Notifications When New Study From this AE is received – If this feature is enabled, and a new Dicom study is received from this AE with the Referring Physician's Name matching with one of the web user's first and last names, MedDream PACS will send a notification email to that user's email address (if defined) about the newly received study.
- Compress images received from this AE – If a Dicom compression transfer syntax is defined for this AE, MedDream PACS will automatically compress any uncompressed Dicom images received from this AE using the defined Dicom compression transfer syntax, so that the compressed Dicom images can be delivered to the web viewers than the uncompressed images.
- Anonymize studies received from this AE – If this option is enabled, MedDream PACS will anonymize studies received from this source AE by the syntax rules pre-defined in a template selected by the user.
- Assign Dicom Studies Received From This AE To Web Users – The Administrator can enable this option and assign one or more web users to a Source AE defined in the **Application Entity** table, so that the web users assigned to this Source AE can access all Dicom studies received from this Source AE, even if the assigned web users do not have the 'View' privilege to access private studies, or their registered last and first names do not match with either the **Referring Physician's Name** or the **Reading Physician's Name** of the received Dicom study.

- Use [Transcription Template for Dicom Studies Received from this AE](#) – If this option is enabled, MedDream PACS will assign the selected transcription template for any Dicom study received from this source AE, so that the web users can download the Microsoft Word document template with the pre-configured bookmarks automatically filled-in with information from that Dicom study.

## SCP Application Entities

In addition to the columns common to the Application Entity table, i.e., AE Title, Hostname, IP Address, the following SCU specific values will be displayed in the [Application Entity Table](#) page if the AE is a SCP:

- [Verify Connection](#) – Clicking on the [ping](#) link will verify if the remote SCP can accept DICOM association requests by sending a C-ECHO request to the specified TCP port number. If the C-ECHO is accepted successfully, a pop-up message box will be displayed to indicate confirmation for the C-ECHO request. Otherwise, an error page will follow with any possible source or reason for the failure.
- [Remote Exams](#) – Clicking on the [query/Retrieve](#) link will display the [Search Remote PACS Database](#) page as illustrated below:

MedDream PACS | About | Logout root @ PACS

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Softmca

Search Remote Application Entity: [premium](#)

- [List All Patients](#)
- [Search By Patient Attribute\(s\)](#)

Patient ID:  [Search](#)

Patient Name:

Last:  First:  [Search](#)
- [List All Studies](#)
- [Search By Study Attribute\(s\)](#)

Study ID:  [Search](#)

Accession Number:  [Search](#)

Referring Physician:

Last:  First:  [Search](#)

Study Date: [Search](#)

Today

Yesterday

On This Date:  (YYYY-MM-DD Format)

From:  (YYYY-MM-DD Format) To:  (YYYY-MM-DD Format)

Figure 10 Search Remote PACS Database

---

Where you can search by using the following criteria:

- List All Patients – Selecting this option will send a Patient-Root Information Model C-FIND request with **Universal Matching** for the Patient ID attribute to the remote Query/Retrieve SCP.
- Search By Patient Attributes – You can search either by Patient ID or Patient Name attribute, wild-card characters '\*' (one or more characters) and '?' (Any single character) are supported. If wild-card characters are used, then a C-FIND request with **Wild-Card Matching** for either the Patient ID or Patient Name attribute will be sent to the remote Query/Retrieve SCP. Otherwise, **Single Value Matching** will be used instead.
- List All Studies – Selecting this option will send a Study-Root Informational Model C-FIND request with **Universal Matching** for the Study UID attribute to the remote Query/Retrieve SCP.
- Search By Study Attributes – You can search by Study ID, Accession Number, Referring Physician's Name or Study Date. Wild-Card characters are supported for searching by Study ID, Accession Number or Referring Physician's Name. **Wild-Card Matching** will be used in the C-FIND request if wild-card characters are used when searching for Study ID, Accession Number or Referring Physician's Name, **Single Value Matching** will be used otherwise. **Single Value Matching** will be used when searching by Study Date for Today, Yesterday or a particular fixed date; **Range Matching** will be used otherwise when searching by Study Date.
- Search By Series Attributes – You can search by Modality or Series Date. Wild-Card characters are supported for searching by Modality. **Wild-Card Matching** will be used in the C-FIND request if wild-card characters are used when searching for Modality, **Single Value Matching** will be used otherwise. **Single Value Matching** will be used when searching by Series Date for Today, Yesterday or a particular fixed date; **Range Matching** will be used otherwise when searching by Series Date.
- Modality Worklist – Clicking on the Get Worklist link will initiate a DICOM Worklist-FIND command to the remote Worklist SCP and display any worklist item(s) retrieved from the remote AE.
- Printer Properties – Clicking on the Printer Properties link will initiate a DICOM N-GET command to the remote Dicom printer and retrieve the properties and current status information of the remote printer.

### Modality Worklist SCP Application Entities:

If the '**WorklistScp**' attribute is set to '**True**' for a specified AE in the Application Entity table, MedDream PACS will poll the corresponding Worklist SCP periodically to retrieve worklist items using a pre-defined interval. The default polling interval is 10 minutes, and this interval is configurable by modifying the following Windows Registry value:

```
HKEY_LOCAL_MACHINE\Software\Softneta\MedDream PACS\{AETITLE}\WorklistPollInterval
```

Where:

{AETITLE} is the Application Entity Title you have assigned for MedDream PACS during installation.

Additionally, if MedDream PACS receives DICOM N-EVENT-REPORT **Study Scheduled** event notifications from remote Detached Study Management SCP applications, MedDream PACS will query any defined Modality Worklist SCP application entity (s) for the relevant study information contained in the **Study Scheduled** event report notification.

By default, MedDream PACS queries the remote Worklist SCP with the **Scheduled Procedure Start Date** filter of **Today's Date**, i.e., MedDream PACS will query the remote Worklist SCP for all procedures that are scheduled to start today or later. If you want MedDream PACS to also query for procedures scheduled for the last N days as well, you can add or set the following Windows Registry value:

```
HKEY_LOCAL_MACHINE\Software\Softneta\MedDream PACS\{AETITLE}\WorklistPollPeriod
```

Where:

---

{AETITLE} is the Application Entity Title you have assigned for MedDream PACS during installation.

Set the DWORD value to N if you want MedDream PACS to include the procedures scheduled in the last N days when it queries the remote Worklist SCP. If you want MedDream PACS to query for all scheduled worklist data from the remote Worklist SCP, you can set this DWORD value to 0xFFFFFFFF (-1).

## Pre-Fetching of Dicom Studies for Scheduled AE Station

When MedDream PACS retrieves worklist information for a scheduled patient and the scheduled AE station is defined in the Application Entity table of MedDream PACS, then MedDream PACS will automatically push any pre-existing studies of this patient of the same modality information to the scheduled AE station, so that the scheduled AE station won't have to fetch them manually from MedDream PACS if it wants to access prior studies of the scheduled patient.

This Pre-Fetching feature is enabled by default. To disable it, the following Registry DWORD value must be defined:

```
HKEY_LOCAL_MACHINE\Software\Softneta\MedDream PACS\{AETITLE}\PrefetchStudiesFromWorklist
```

Where:

{AETITLE} is the Application Entity Title you have assigned for MedDream PACS during installation. The above DWORD value must be explicitly set to 0 in order to disable the Pre-Fetching feature.

## Query/Retrieve SCP Application Entities:

If the '**Query/Retrieve Scp**' attribute is set to '**True**' for a specified AE in the Application Entity table, users can optionally enable the Remote Study Synchronization feature by choosing from one of the following option boxes:

- Do Not Synchronize Remote Studies – This feature will be disabled.
- Synchronize Remote Studies On the Following 24 Hour Schedule – Users can choose up to 24 hourly schedules for MedDream PACS to synchronize remote studies stored on this remote AE. Users can further choose from the following synchronization methods:
  - Synchronize All Remote Studies – MedDream PACS will query (C-FIND) this remote AE and find all studies that are not currently in the local MedDream PACS Serve database, MedDream PACS will then fetch (C-MOVE) those studies from this remote AE.
  - Synchronize Remote Studies Received within the Last [N] Days – MedDream PACS will query (C-FIND) this remote AE and find all studies that were recently received within the last N days, MedDream PACS will then fetch (C-MOVE) those studies from this remote AE.
  - Update Existing Studies If Already Exist – If this checkbox is selected, MedDream PACS will retrieve studies stored in this remote AE, even if they already exist in the current MedDream PACS database.

Users can visit the '**Job Status**' page to check the status of these scheduled remote synchronizations on a daily basis.

- Mark Retrieved Studies as Read – If this feature is enabled, MedDream PACS will mark a study as **Read** after it has been retrieved or moved to this destination AE.
- Job Queue Priority – This is the priority when processing database jobs for this destination AE. The default value is 0 which means **Normal** priority. Database jobs with higher priority destination AEs will be processed before those jobs with lower priority destination AEs.

---

### **AE Group Settings:**

If an Application Entity (AE) is configured as an AE Group with one or more application entities as members, then this group AE can be used as a round-robin distribution group when it's configured as the Destination AE for an automatic routing rule with the "Wait N Minutes and Forward the Entire Study" option enabled. For example, if an AE group consists of 3 individual member AEs: AE#1, AE#2 and AE#3 and this AE group is configured as the Destination AE for an automatic routing rule with the "Wait N Minutes and Forward the Entire Study" option enabled, then the 1<sup>st</sup> matching study received will be forwarded to AE#1, the 2<sup>nd</sup> matching study received will be forwarded to AE#2, the 3<sup>rd</sup> matching study received will be forwarded to AE#3, the 4<sup>th</sup> matching to AE#1, the 5<sup>th</sup> to AE#2, the 6<sup>th</sup> to AE#3, etc. So in summary, the AE group serves as the round-robin distribution method to forward matching studies received to all member AEs.

---

## HL7 Applications (optional)

This page will be displayed if the optional HL7 Message Listener module is installed along with MedDream PACS Premium Edition, where the users can add, modify or delete defined HL7 applications:

- `Application Name` - Name of this HL7 application. This name is used as the key to the HL7 Application table, so multiple HL7 applications cannot share the same name.
- `Facility` - Facility of this HL7 application.
- `Description` - Description of this HL7 application.
- `Hostname` - Name of the host where this HL7 application is running.
- `IP Address` - If DNS hostname is not configured above, then a static or dynamic IP address can be configured here.
- `Port Number` - TCP port this HL7 application listens to for incoming connections.
- `Maximum Number of Simultaneous Connections` - The maximum number of simultaneous connections that MedDream PACS will establish with this HL7 application at any time. Default value is 10.
- `Enable ORU Report Notification Message for Newly Received Dicom Studies` - If this option is enabled, MedDream PACS will send a HL7 ORU message to this HL7 application with the URL for accessing newly received Dicom studies when they are received for the very first time.

MedDream PACS | About | Logout root @ demo      User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | HL7 Application | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

There are 0 HL7 Applications defined.

Application	Facility	Description	Host	IP Address	Port Number	Maximum Connections	ORU Report	Edit
-------------	----------	-------------	------	------------	-------------	---------------------	------------	------

Add

Figure 11 HL7 Applications (optional)

---

## Searching MedDream PACS Database

Clicking on the **'Search'** link from the Main Menu bar will display the 'Search Local MedDream PACS Database' page, which is similar to the 'Search Remote PACS Database' page above, where users can search by patient, study, series or image attributes.

The screenshot displays the 'Search By Patient' section of the MedDream PACS interface. The top navigation bar includes links for 'User Administration', 'Configuration', 'Email', 'Journal', 'Home', 'Unread Studies', 'Browse', 'Search', 'Dicom AE', 'Auto Route', 'Job Status', 'Modality Worklist', 'Tools', 'Profile', and 'Help'. The 'Search By Patient' tab is active, with other tabs for 'Search By Study', 'Search By Series', 'Search By Image', 'Search Modality Worklist', 'Search Registered User', and 'Search Dicom AE' visible. The search form includes the following fields:

- Patient ID:** A text input field with a checkbox labeled 'Append wild-card character \* to search pattern'.
- Patient Name:** A section containing:
  - Lastname:** A text input field with a checkbox labeled 'Append wild-card character \* to search pattern'.
  - Firstname:** A text input field with a checkbox labeled 'Append wild-card character \* to search pattern'.
  - Full Name Search (ignore order of first, middle and last names):** A wide text input field.
- Date of Birth:** A section with two date pickers:
  - From:** A date picker with a dropdown arrow and a format hint '(YYYY-MM-DD Format)'.
  - To:** A date picker with a dropdown arrow.
- Institution Name:** A text input field.
- Study Date:** A section with two date pickers:
  - From:** A date picker with a dropdown arrow and a format hint '(YYYY-MM-DD Format)'.
  - To:** A date picker with a dropdown arrow and a format hint '(YYYY-MM-DD Format)'.
- Search By Patient:** A button to execute the search.

Figure 12 Search MedDream PACS Database

---

## Navigating MedDream PACS Web User Interface

After a MedDream PACS user account has been created successfully by the Administrator/Super-user ('root' for MySQL or 'SYSTEM' for Oracle databases) in [Section 0](#), the user can access the MedDream PACS web user interface from any web browser, by logging into MedDream PACS from the URL below:

`http://{HOSTNAME}/MedDream_PACS/home.php`

NOTE: {HOSTNAME} is the name of the machine where MedDream PACS is installed.

### Login Page

Before any of the MedDream PACS web user interface pages can be accessed, the user needs to be authenticated through the Login Page below, where a valid MySQL username and password must be specified:



User [root] has logged out successfully.

Current Database:

Enter Username:

Enter Password:

Enter Anti-Spam Code From Below:

\*\*\* Anti-Spam Code: 1339 \*\*\*

Not a registered user?

Figure 13 Login Page

---

## Home Page (Today's Study Page)

After the user has been authenticated by the Login Page, the Home Page will be displayed below which contains a list of accessible studies received today:

MedDream PACS | About | Logout root @ demo

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Softmeda

11 most-recently received accessible studies:

Previous 1 2 Next

Display All | Displaying 1-10 of 11 Studies

Check All Forward Delete Export Download Change Storage Mark Study As Un-Read Show Filters

Privacy	Patient ID	Patient Name	Patient's Sex	Date of Birth	Age	Institution Name	Study ID	Study Date	Study Time	Received On	Accession Number	Referring Physician's Name	Description	Reading Physician's Name	Read By	Requesting Physician's Name	Source AE	Total Number of Instances
---------	------------	--------------	---------------	---------------	-----	------------------	----------	------------	------------	-------------	------------------	----------------------------	-------------	--------------------------	---------	-----------------------------	-----------	---------------------------

Figure 14 Home Page (Today's Study Page)

## Main Menu Bar

This navigation menu bar is displayed at the top of every MedDream PACS user interface, with the left side displaying the current logged-in user and right side displaying the following navigational links:

- [User Administration](#) – This link is displayed only if the current user is the Administrator/Super-user ('root' for MySQL or 'SYSTEM' for Oracle databases), clicking on this page will display the main `User Administration` page.
- [Configuration](#) – This link is displayed only if the current user is the Administrator/Super-user ('root' for MySQL or 'SYSTEM' for Oracle databases), clicking on this page will display the main `System Configuration` page.
- [Email](#) – This link is displayed only if the current user is the Administrator/Super-user ('root' for MySQL or 'SYSTEM' for Oracle databases), clicking on this page will display the main `SMTP Server Configuration` page.
- [Journal](#) – This link is displayed only if the current user is the Administrator/Super-user ('root' for MySQL or 'SYSTEM' for Oracle databases), clicking on this page will display the main `System Journal Log` page.
- [Home](#) – Clicking on this link will display the `Today's Study` page.
- [Unread studies](#) – Clicking on this link will display a list of unread studies in the database.
- [Browse](#) – Clicking on this link will display a list of all accessible patients in the database.
- [Search](#) – Clicking on this link will display the `Search Local MedDream PACS Database` page.
- [Dicom AE](#) – Clicking on this link will display the `Application Entity Table` page.
- [HL7 Applications \(optional\)](#) – Clicking on this link will display the `HL7 Application Table` page.
- [Auto Route](#) – Clicking on this link will display the `Automatic Routing` page.
- [Job Status](#) – Clicking on this link will display the current scheduled database job status for the current user.
- [Modality Worklist](#) – Clicking on this link will display the `Modality Worklist Table`.
- [Tools](#) – Clicking on this link will display the `Tools` page.
- [Profile](#) – Clicking on this link will display the `User Profile` page.

- [Help](#) – Clicking on this link will display this document.
- [Logout](#) – Clicking on this link will logout current user and go back to the MedDream PACS Login page.

## Unread Studies Page

This page displays the current list of unread studies in the MedDream PACS database. Note that studies displayed in this page are high-lighted with the **Un-read** color background.

Privacy	Patient ID	Patient Name	Patient's Sex	Date of Birth	Age	Institution Name	Study ID	Study Date	Study Time	Received On	Accession Number	Referring Physician's Name	Description	Reading Physician's Name	Read By	Requesting Physician's Name	Source AC	Total Number of Instances
Private <a href="#">Change to Public</a>	123444	Hubert Elaine Wolfeschlegelsteinhausenbergerdorff sr	M	1904-02-29	N/A	N/A	2016007121041	2016-05-07	12:10:41	2016-06-07 12:26:54	2016007321041	N/A	N/A	N/A	N/A	N/A	SENDTOPACS	1
Private <a href="#">Change to Public</a>	Q	Anonymized	M	N/A	29	N/A	1	2016-04-19	09:17:00	2016-05-26 13:11:28	N/A	N/A	UPPER GI / SW UPPER TRIM / AIR	N/A	N/A	N/A	SENDTOPACS	1
Private <a href="#">Change to Public</a>	NONE	Nona Name	O	N/A	25	N/A	<a href="#">Study Details</a>	2016-06-05	16:52:15	2016-05-29 13:11:27	N/A	N/A	US ABDOMEN LTD	N/A	N/A	N/A	SENDTOPACS	1

Figure 15 Unread Studies Page

## Browse Page

This page displays a list of accessible patients for the current user, with the following patient-specific information depending on the privilege level of the current user:

Privacy	Patient ID	Patient Name	Date of Birth	Patient's Sex	Age	Number of Studies	Details
Private <a href="#">Change to Public</a>	123444	Hubert Elaine Wolfeschlegelsteinhausenbergerdorff sr	1904-02-29	M	N/A	1	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	Q	Anonymized	N/A	M	29	5	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	NONE	Nona Name	N/A	O	20	1	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	11410	Zalockiana janina	1949-04-12	F	N/A	1	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	R	RR	N/A	N/A	N/A	1	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	CR15-193813	Kirkiene janina	1954-01-23	F	61	1	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	35501251240	Blakisev vladimir	1955-01-25	M	60	1	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	HE15-8648	Zaludevas nikolajus	1953-05-18	M	62	1	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	E15-29288	Valerijana Oramyko	1937-08-28	F	78	1	<a href="#">More Information</a>
Private <a href="#">Change to Public</a>	839730	Helgard Musterfrau	1953-04-18	F	59	1	<a href="#">More Information</a>

Figure 16 Browse Page

- **Privacy** – This is the privacy attribute of the patient (s). This column is displayed only if the current user has the **'Modify'** privilege **'Enabled'**. Clicking on the **'Change to Public'** or **'Change to Private'** will toggle the privacy setting for the patient.
- **Patient ID** – Patient ID. Clicking on this link will display the **Study** page described below in [Section 0](#), for all studies belong to this patient.
- **Patient Name** – Name of the patient.
- **Date of Birth** – Patient's Birth Date.
- **Patient's sex** – Sex of the patient.
- **Age** – Patient's age.
- **Number of studies** – This is the number of studies made to the patient.
- **Details** – Clicking on this link will display a much detailed information about the patient and the study itself such as middle name, address, comments, height, weight, occupation, history, etc.
- **Download** – This link is **'Enabled'** only if the current user has the **'Download'** privilege is **'Enabled'**. Clicking on this link will download all images of this patient compressed into a ZIP file to the web browser.
- **Check All/Uncheck All** – This button is displayed only if the current user has the **'Modify'** privilege **'Enabled'**. Clicking on the **'Check All'** or **'Uncheck All'** button toggles between selecting all patients and un-selecting all patients.
- **Forward** – This button is displayed only if the current user has the **'Modify'** privilege is **'Enabled'**. Clicking on this button will display the **'Forward Images'** page, which is described in [Section 0](#) below for forwarding all images of the selected patient (s) to a remote SCP.
- **Delete** – This button is displayed only if the current user has the **'Modify'** privilege is **'Enabled'**. Clicking on this button will pop-up a message box asking for confirmation to delete the selected patient (s) from the MedDream PACS database. If confirmed, the selected patient (s) will be removed from the MedDream PACS database.
- **Print** – This button is displayed only if the current user has the **'Print'** privilege is **'Enabled'**. Clicking on this button will print the selected patients to the destination printer and printing format selected by the user.
- **Export** – This button is displayed only if the current user has the **'Export'** privilege is **'Enabled'**. Clicking on this button will export the selected patients into a destination folder specified by the user, using the Dicom standard Part 10 directory format (**DICOMDIR**) for media interchange.

## Study Page

MedDream PACS | About | Logout root @ demo

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

There are 1 accessible studies for Patient: Hubert.Slone.Wolfeschleichenhausen@kerckhoff.de

Previous Next

Displaying 1-1 of 1 Studies

Check All Forward Delete Export Download Change Storage Mark Study As Read

Privacy	Study ID	Study Date	Study Time	Received On	Accession Number	Referring Physician's Name	Description	Reading Physician's Name	Read By	Requesting Physician's Name	Source AE	Total Number of Instances
Private Change to Public	20160807121841	2016-08-07	12:18:41	2016-08-07 12:26:54	20160807121841	N/A	N/A	N/A	N/A	N/A	SENDTOPACS - SENDTOPACS	1

Check All Forward Delete Export Download Change Storage Mark Study As Read

Figure 17 Study Page

---

This page displays a list of accessible studies of a patient for the current user, with the following study-specific information depending on the privilege level of the current user:

- **Public/Private** – This is the privacy attribute of the study (s). This column is displayed only if the current user has the '**Modify**' privilege 'Enabled'. Clicking on the 'Change to Public' or 'Change to Private' will toggle the privacy setting for the study.
- **ID – Study ID**. Clicking on this link will display the *Series* page described below in [Section 0](#), for all series belong to this patient.
- **Date – Study date**.
- **Time – Study time**.
- **Accession Number – Accession Number**.
- **Modalities** – A list of modalities in the study.
- **Referring Physician** – Name of the referring physician.
- **Description** – Study description.
- **Reading Physician** – Name of physician reading the study.
- **Admitting Diagnoses** – Admitting diagnoses.
- **Interpretation Author** – Name of the interpretation author.
- **Download** – This link is 'Enabled' only if the current user has the '**Download**' privilege is 'Enabled'. Clicking on this link will download all images of this study compressed into a ZIP file to the web browser.
- **Check All/Uncheck All** – This button is displayed only if the current user has the '**Modify**' privilege 'Enabled'. Clicking on the '**Check All**' or '**Uncheck All**' button toggles between selecting all studies and unselecting all studies.
- **Forward** – This button is displayed only if the current user has the '**Modify**' privilege is 'Enabled'. Clicking on this button will display the '**Forward Images**' page, which is described in Section 10 below for forwarding all images of the selected study (s) to a remote SCP.
- **Delete** – This button is displayed only if the current user has the '**Modify**' privilege is 'Enabled'. Clicking on this button will pop-up a message box asking for confirmation to delete the selected study (s) from MedDream PACS database. If confirmed, the selected patient (s) will be removed from the MedDream PACS database.
- **Print** – This button is displayed only if the current user has the '**Print**' privilege is 'Enabled'. Clicking on this button will print the selected studies to the destination printer and printing format selected by the user.
- **Export** – This button is displayed only if the current user has the '**Export**' privilege is 'Enabled'. Clicking on this button will export the selected studies into a destination folder specified by the user, using the Dicom standard Part 10 directory format (**DICOMDIR**) for media interchange.

## Series Page

MedDream PACS | About | Logout root @ PACS

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Softmeta

There is 0 note for this study

Add

There are 1 series in Study: 1.2.250.1.59.913.9.11.11.7.11.1 for Patient: [Alberto Pujá garcía](#)

Previous Next

Displaying 1-1 of 1 Series:

Check All Forward Delete Export Download

Series Number	Date	Time	Modality	Body Part	Operator Name	Total Instances	Description
<input type="checkbox"/> <a href="#">1001</a>	2007-11-11	14.07.04	CR	CHEST	N/A	1	N/A

Check All Forward Delete Export Download

Figure 18 Series Page

This page displays a list of series of the selected study for the current user, with the following series-specific information depending on the privilege level of the current user:

- **Series Number** – Series Number. Clicking on this link will display the **Image** page.
- **Date** – Series date.
- **Time** – Series time.
- **Modality** – Modality of the series.
- **Body Part** – Body part.
- **Operator name** – name of the operator.
- **Total Instances** – Total number of images in this series.
- **Description** – Series description.
- **Download** – This link is 'Enabled' only if the current user has the 'Download' privilege is 'Enabled'. Clicking on this link will download all images of this series compressed into a ZIP file to the web browser.
- **Check All/Uncheck All** – This button is displayed only if the current user has the 'Modify' privilege 'Enabled'. Clicking on the 'Check All' or 'Uncheck All' button toggles between selecting all series and unselecting all series.
- **Forward** – This button is displayed only if the current user has the 'Modify' privilege is 'Enabled'. Clicking on this button will display the 'Forward Images' page.
- **Delete** – This button is displayed only if the current user has the 'Modify' privilege is 'Enabled'. Clicking on this button will pop-up a message box asking for confirmation to delete the selected series from MedDream PACS database. If confirmed, the selected series will be removed from the MedDream PACS database.
- **Print** – This button is displayed only if the current user has the 'Print' privilege is 'Enabled'. Clicking on this button will print the selected series to the destination printer and printing format selected by the user.
- **Export** – This button is displayed only if the current user has the 'Export' privilege is 'Enabled'. Clicking on this button will export the selected series into a destination folder specified by the user, using the Dicom standard Part 10 directory format (**DICOMDIR**) for media interchange.

This page also displays a list of user notes about the subject study on the Left Panel, where the logged-in user can add discussion notes about this study by clicking on the 'Add' button.

## Study Notes Page

This page is used for registered users to exchange discussion notes about a subject study. Users can add, modify or delete notes with a subject headline and detailed text notes as bulletin-board style discussions about the subject study. Users with 'Upload' privilege can also upload text files, zip files, PDF/Word documents, as well as audio/video clips as attachments to the related study notes.

Figure 19 Add Study Notes

From the "Add Study Notes" page above, users can enter discussion notes about this study, and each note consists of the following information:

- Subject Headline – Any text of up to 64 characters
- Details Notes – Any text of up to 512 characters
- Attachments – If the logged-in user has the 'Upload' privilege enabled, users can upload additional files such as text files, PDF/Word documents, zip files, audio/video clips, etc. of maximum file size allowed for file uploads. This limit is controlled by the smaller value of the following two variable:
  - \$MAX\_UPLOAD\_LIMIT system configuration variable.
  - upload\_max\_filesize variable in your 'PHP.INI' file

Subject	User	When	Notes	Attachments	Action
<input type="checkbox"/> Study Note 1	root	2016-06-20 14:33:12	Some detailed notes about this study can be put here.	20160620-143304-root-20160616-160245-study.txt (0 bytes)	<a href="#">Edit</a>

Figure 20 Study Notes Page

This page is the where all the discussion notes about this subject study are listed. If the logged-in user has the 'Modify' privilege enabled, the user can delete any notes on this page. Otherwise, the user can only delete those notes entered by the user himself/herself. The user can also modify any note which was previously entered by himself/herself by clicking on the 'edit' link.

## Structured Reports

If the selected study contains any DICOM Structured Report (SR), they will also be displayed as separate series along with the regular imaging series of the selected study.

MedDream PACS | About | Logout root @ PACS User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

---

Patient ID:	GE0514
Patient Name:	CHARLES WILKINS
Referring Physician:	S LISOOK <sup>MD</sup>
Study ID:	1784
Series Number:	1
Instance Number:	1
Completion Flag:	PARTIAL
Completion Flag Description:	N/A
Verification Flag:	UNVERIFIED
Content Date:	2004-05-11
Content Time:	00:31:19

---

### CT Report

- Contains
- **Request**  
CT: Abdomen
- **History**  
Patient is a 45 year old male with abnormal liver function test. Ultrasound evaluation demonstrated a 3 cm lesion in the medial aspect of the right lobe of the liver. The question was raised regarding potential hemangioma.
- **Procedure**  
Serial imaging was obtained in the upper abdomen with the administration of oral and intravenous contrast.
- **Finding**  
The examination demonstrates a well circumscribed 3 cm lesion present within the medial aspect of the inferior right liver lobe. Initial evaluation demonstrates lack of contrast enhancement. Subsequent imaging (not shown) demonstrated typical contrast enhancement pattern of a benign hemangioma of the liver. The remaining contrast enhancement pattern in the liver is normal. There is normal appearance of the adrenal glands, spleen, kidneys, and pancreas. There is no evidence of liver metastasis. 3 cm nodule present in the inferior medial aspect of right liver lobe. Contrast enhancement pattern

Figure 21 Structured Report Page

If the structured report document contains reference(s) to any image instances and they are accessible in the MedDream PACS database, a URL link to each referenced image instance will be displayed instead of the plain instance UID string.

## Image Page (Thumbnail)



Figure 22 Image Page (Thumbnail)

This page displays a list of images of a selected series for the current user, with the following image-specific information depending on the privilege level of the current user:

- **Thumbnail Image** – Clicking on the thumbnail image will display the 'Full Size Image' page, instead of the thumbnail image displayed in the current page.
- **Instance #** – Clicking on this link will display all the Dicom attributes (tags) encoded in the raw image file.
- **Check All/Uncheck All** – This button is displayed only if the current user has the '**Modify**' privilege 'Enabled'. Clicking on the '**Check All**' or '**Uncheck All**' button toggles between selecting all images and un-selecting all images.
- **Delete** – This button is displayed only if the current user has the '**Modify**' privilege is 'Enabled'. Clicking on this button will pop-up a message box asking for confirmation to delete the selected image(s) from MedDream PACS database. If confirmed, the selected image(s) will be removed from the MedDream PACS database.
- **Download** – This button is 'Enabled' only if the current user has the '**Download**' privilege is 'Enabled'. Clicking on this button will download the selected images compressed into a ZIP file to the web browser.
- **Show** – If the Java Applet Viewer (e.g. the AiViewer, the Radscaper, or RemotEye Viewer) or the Active-X Viewer (e.g. iQ-X) is installed properly, this button will be displaying and clicking on this button will launch the Java Applet Viewer application.
- **Tag/Un-Tag** – Clicking on the '**Tag**' button will mark the selected images as key images, while clicking on the '**Un-Tag**' button will un-mark the selected images as key images.
- **Print** – This button is 'Enabled' only if the current user has the '**Print**' privilege is 'Enabled'. Clicking on this button will download print the selected images to a Dicom printer
- **Export** – This button is 'Enabled' only if the current user has the '**Export**' privilege is 'Enabled'. Clicking on this button will export the selected images into a Dicom Part-10 formatted destination folder.

## Image Page (Full Size)

MedDream PACS | About | Logout root @ PACS

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Softneta

There is 0 note for this image

Add

Patient: ANNA NEUBAUER Study: 000004 Series Number: 1 Instance Number: 13

75% Smaller 50% Smaller 25% Smaller Original Size 25% Larger 50% Larger 75% Larger

Next

Next

Online Image Processing

Email JPG Image To: (Separate multiple email addresses with comma ',')

Figure 23 Image Page (Full Size)

This page displays the selected image in its original size, with the following navigation links:

- **Previous** – This link will be displayed if there is an image within the same series with a smaller instance number than the currently displayed image. Clicking on this link will scroll **backward** to display the image with the largest instance number lower than the current instance.
- **Next** – This link will be displayed if there is an image within the same series with a bigger instance number than the currently displayed image. Clicking on this link will scroll **forward** to display the image with the smallest instance number higher than the current instance.
- **Previous Series** – This link will be displayed if there is another series within the same study with a smaller series number than the currently displayed series. Clicking on this link will scroll **backward** to display the series with the largest series number lower than the current series.
- **Next Series** – This link will be displayed if there is another series within the same study with a bigger series number than the currently displayed series. Clicking on this link will scroll **forward** to display the series with the smallest series number higher than the current series.
- **Online Image Processing** – Clicking on this button will display the 'Online Image Processing' page.
- **Email JPG Image** – Clicking on this button will send the converted JPG or GIF image being displayed to the registered email address of the current user. Users can also enter the destination email address in the "To:" field, and multiple email addresses can be entered by using the comma (",") as the separator.

This page also displays a list of user notes about the subject image on the left panel, where the logged-in user can add discussion notes about this image by clicking on the 'Add' button.

---

## Image Notes Page

This page is used for registered users to exchange discussion notes about a subject image. Users can add, modify or delete notes with a subject headline and detailed text notes as bulletin-board style discussions about the subject image. Users with 'Upload' privilege can also upload text files, PDF/Word documents, as well as audio/video clips as attachments to the related image notes.

MedDream PACS | About | Logout root@PACS

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Softneta

Patient ID: SM551104  
Patient Name: JIMBA, NPJRAUER  
Study ID: 000004  
Study Date: 1994-06-10  
Accession Number: SM5000013  
Study Description: OFFIS Structured Reporting Samples  
Series Number: 0  
Series Date:   
Modality: MR

Enter Subject Headline (up to 64 characters):

Enter Detailed Notes About This Image:

Attach (max 2 Mb) Browse...

Attachment:  PACS\_Charts.pdf (647738 bytes)

Unattach

Add

Figure 24 Add Image Notes

From the “Add Image Notes” page above, users can enter discussion notes about this image, and each note consists of the following information:

- Subject Headline – Any text of up to 64 characters
- Details Notes – Any text of up to 512 characters
- Attachments – If the logged-in user has the 'Upload' privilege enabled, users can upload additional files such as text files, PDF/Word documents, zip files, audio/video clips, etc. of maximum file size allowed for file uploads. This limit is controlled by the smaller value of the following two variable:
  - `$MAX_UPLOAD_LIMIT` system configuration variable.
  - `upload_max_filesize` variable in your 'PHP.INI' file

MedDream PACS | About | Logout root @ PACS

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Softmeta

Patient ID: [EM5511104](#)  
 Patient Name: ANDIA NEUBAUER  
 Study ID: [000001](#)  
 Study Date: 1994-06-13  
 Accession Number: SB 5900013  
 Study Description: OFHS Structured Reporting Samples  
 Series Number: 1  
 Series Date:  
 Modality: MR

Subject	User	When	Notes	Attachments	Action
<input type="checkbox"/> Image Note 1	root	2005-11-06 16:38:30	Detailed notes about this image	N/A	N/A
<input type="checkbox"/> Image Note 2	pacsona	2005-11-06 16:37:37	Detailed discussions about this image	<a href="#">20051106-163734-PACS_Charts.pdf (647738 bytes)</a>	<a href="#">Edit</a>

[Check All](#) [Add](#) [Delete](#)



Figure 25 Image Notes Page

This page is the where all the discussion notes about this subject image are listed. If the logged-in user has the 'Modify' privilege enabled, the user can delete any notes on this page. Otherwise, the user can only delete those notes entered by the user himself/herself. The user can also modify any note which was previously entered by himself/herself by clicking on the [Edit](#) link.

## Online Image Processing Page



Window/Level	Image pixel grayscale values range from 0 (darkest) to 100 (brightest) Window size: <input type="text" value="100"/> from 1 to 100 Level: <input type="text" value="50"/> from 0 to 100	<input type="button" value="Window/Level"/>
Gamma Correction	Gamma correction value: <input type="text" value="1.5"/> typical range from 0.8 to 2.3	<input type="button" value="Gamma"/>
Contrast	<input checked="" type="radio"/> Increase <input type="radio"/> Decrease	<input type="button" value="Contrast"/>
Edge Enhancement	Select radius from 1 to 10 pixels: <input type="text" value="2"/>	<input type="button" value="Enhance"/>
Resize Image	<input checked="" type="radio"/> Width: <input type="text" value="512"/> Height: <input type="text" value="512"/> <input type="radio"/> 2x Zoom	<input type="button" value="Resize"/>
Enhance Image	Apply digital filtering to improve the quality of a noisy image	<input type="button" value="Image Enhancement"/>
Equalize Image	Apply histogram equalization to the image	<input type="button" value="Equalize"/>
Invert Image	<input checked="" type="radio"/> Invert only grayscale values within the image <input type="radio"/> Invert all grayscale values	<input type="button" value="Invert"/>
Normalize Image	Enhance contrast of images by normalizing pixel grayscale values	<input type="button" value="Normalize"/>
Rotate Image	Rotate: <input type="text" value="90"/> degrees <input checked="" type="radio"/> Clockwise <input type="radio"/> Counter-clockwise	<input type="button" value="Rotate"/>
Original Image	Display the stored original image	<input type="button" value="Original Image"/>

Figure 26 Online Image Processing Page

This page offers the following set of image processing tools, with the processed image displayed on the left and a reference image (original) displayed on the right:

- Window/Level
- Gamma Correction
- Contrast
- Edge Enhancement
- Resize Image – Resize image in absolute pixels or simple 2x zoom
- Enhance Image – Remove image noise
- Equalize Image – Apply histogram equalization to the image
- Invert Image

- `Normalize Image` – Normalize grayscale values of image pixels
- `Rotate Image`
- `Original Image` – Switch back to the original image

## Tools Page



Figure 27 Tools Page

This page contains the following useful utilities that enhance the functionalities of MedDream PACS Premium Edition:

### Custom Data Element Coercion

This tool allows MedDream PACS users to define a custom data element coercion pattern for images received from a source AE. The following data elements can be coerced based on the specified coercion pattern:

- `Patient ID (0x00100020)`
- `Modality (0x00080060)`
- `Institution Name (0x00080080)`
- `Accession Number (0x00080050)`
- `Ethnic Group (0x00102160)`




Figure 28 Data Element Coercion Page

The coercion pattern syntax specifies the pattern string to be coerced into, and wild-card characters ‘\*’ and ‘?’ are supported.

For example, if users want to have a prefix string “ABC” inserted to the Patient ID data element for images received from a source AE “XYZ”, before the images are stored in the MedDream PACS database. They can add a data element coercion rule with the following fields:

- Source Application Entity Title - It will be set to “XYZ” in this example
- Data Element Tag - Select Patient ID from the Drop-down list box
- Coercion Rule Syntax - It will be set to “ABC\*” in this example meaning to insert the prefix “ABC” before the received Patient ID string
- Description - This field is for display purpose only and can be set to any text string

With the above example coercion rule, an image received from source AE “XYZ” with the Patient ID of “12345” will be received and stored in MedDream PACS database with the Patient ID of “ABC12345”.

To delete a specific data element, you can define a Data Element Coercion rule with the corresponding data element tag, and the coercion rule syntax of “\*->”, so that MedDream PACS will remove the defined data element from the received images from that source AE. Here are some details examples about the coercion rules:

Pattern	Meaning	Example
123-*	Add prefix “123-“ to the existing/received value	With the “123-*” pattern defined as Patient ID coercion rule, the received Patient ID “ABCDE” becomes “123-ABCDE”
*-123	Add suffix “-123” to the existing/received value	With the “*-123” pattern defined as Patient ID coercion rule, the received Patient ID “ABCDE” becomes “ABCDE-123”
*->12345	Replace existing/received value with the fixed string “12345”	With the “*->12345” pattern defined as Patient ID coercion rule, the received Patient ID “ABCDE” becomes “12345”
*->	Delete the existing value	With the “*->” pattern defined as Accession Number coercion rule, the received Accession Number “ABCDE” will be deleted
*->{0-9}	Keep only the numbers (0-9) within the received value string	With the “*->{0-9}” pattern defined as Accession Number coercion rule, the received Accession Number “ABCDE12345” becomes “12345”
*->{A-Z}	Keep only the alphabetic characters (‘A’-‘Z’) within the received value string	With the “*->{A-Z}” pattern defined as Accession Number coercion rule, the received Accession Number “ABCDE12345” becomes “ABCDE”

Table 6 Data Element Coercion Rule Patterns

## Exporting Patients/Studies

This utility allows users to export patients/studies stored in MedDream PACS database to a local directory, using DICOM Media Storage Format (with DICOMDIR directory record). The content of the directory can later be burned into a CD-R/RW, DVD-R/RW/RAM or DVD+R/RW for media interchange.

Users need to enter the following information to export patients/studies:

- **Export Media Type** – Users can choose from CD, DVD or Dual-Layer DVD as media type for export destination. This field is used to determine the sub-directory name for the local export directory, as well as the media storage capacity (650 Mbytes CD, 4.7 GB DVD or 8.5 GB Dual-Layer DVD) when the exported studies need to be split into multiple volumes.
- **Export Directory** – This field defaults to the **'export'** sub-directory where MedDream PACS is installed.
- **Media Label** – This field is limited to 16 characters and is the media label applied to the DICOMDIR directory record when it is written to the final destination media. In case the exported studies require multiple volumes, the volume number will automatically be appended to the media label for each volume. For example, if the specified media label is "LABEL", the selected media type is CD, and the total exported studies span across three volumes, there will be three sub-directories named **'vol1'** through **'vol3'** under the specified destination export directory, with the media label set to **"LABEL-1"** through **"LABEL-3"** accordingly.
- **Compress exported content into ZIP file** – Clicking on this checkbox will compress the exported content into ZIP files, which can be downloaded directly from the **Job Status** page when the Export job is completed.
- **Include External Viewer Program Files From Folder** – Selecting this checkbox will make MedDream PACS include all files as well as sub-directories from the specified folder as part of the export to the destination directory. NOTE: Use caution when selecting this option and be sure not to include the wrong external viewer directory that contains too many files and/or sub-folders, since MedDream PACS will copy **recursively** all files and sub-directories under this viewer directory to the destination folder.
- **Export Studies** – After users have entered the destination directory for selected media type and the media label, they can click on this button to select from a list of patients/studies to export:

MedDream PACS | About | Logout root @ PACS

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Softneta

Database Integrity Check | Transcription Templates | Restart Service | Compress Entire Database | Statistics Reports | **Export** | Import | Data Element Coercion

Automatic Purge Storage Directories | Check Duplicate Patient ID | Anonymization Templates | Upload Dicom Image | Import Worklist | Today's Log | Live Monitor

Export To Local Directory: C:/MedDreamPACS-Premium/PACS/export/

Export Media Size: CD - 650 MB

Media Label:

Compress exported content into ZIP file

Include External Viewer Program Files From Folder:

Purge raw images of study after export

Export Studies

Figure 29 Export Patients/Studies Page

---

Users can select the interested patients/studies by clicking the checkbox at the beginning of each listed study, and click on the 'Update' button to obtain the total number of studies selected and the total storage space required for exporting the selected studies. After selecting the interested patients/studies for export, the users can click on the 'Export' button to start the export, MedDream PACS will assign a database job to perform the export in the background so that it will not tie up the user interface. Users can check the progress of the export job at any time by visiting the 'Job Status' page, using the assigned job ID.

## Importing External Patients/Studies

This utility allows users to import external patients/studies stored in DICOM Media Storage Format compliant (with or without **DICOMDIR** directory record) CD/DVD media into the MedDream PACS database.

Users need to enter the following information to import external patients/studies into the MedDream PACS database:

- **Source Media Type** – This can either be a Local Directory written in the DICOM Media Storage Format (with or without **DICOMDIR** directory record), or a local CD/DVD media drive.
  - If the source media type is a DICOM Media Storage Formatted local directory, MedDream PACS will read the **DICOMDIR** directory record if it is present, parse any raw image file(s) encoded in DICOM Part 10 format recursively under the specified directory into the MedDream PACS database. The database records are linked to the raw image files in the specified directory, so the raw image files do not need to be copied.
  - If the source media type is a local CD/DVD media drive, MedDream PACS will read the DICOMDIR directory record, parse the directory into the MedDream PACS database, and copy the raw image files on the removable media into a destination local directory specified by the user.
- **Destination Directory** – If the specified source media type is a local CD/DVD drive, users will also need to specify a local destination directory to copy the raw images files on the local media to.
- **Import Studies** – After user has entered the information above, user can click on this button to start the import.

When importing external images from a local directory but there is no **DICOMDIR** directory record present in the specified directory, MedDream PACS will display a warning message below before trying to parse recursively any DICOM Part 10 encoded image files stored in the directory into the MedDream PACS database.




Figure 30 Warning Message for Importing without DICOMDIR

MedDream PACS will assign a database job to perform the import in the background so that it will not tie up the user interface. Users can check the progress of the import job at any time by visiting the 'Job Status' page, using the assigned job ID.

## Statistics Reports

This feature allows the Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases) or users with '**view**' privilege to query statistics reports for studies received during different time periods:

- Studies Received Yesterday
- Studies Received This Week
- Studies Received This Month
- Studies Received This Year
- Studies Received During a [**From**, **To**] date window
- Studies Received From a Specific Source AE
- Studies Received From Each Source AE defined in the "**Dicom AE**" page

The Statistics Report page will be displayed after user clicks on the Get Report button. In addition to the study information displayed, the following attributes will be displayed for each study:

- The date the study was received
- The Source AE Title from where the study was received
- The total number of images currently in this study
- The total size of the raw images file currently in this study

MedDream PACS | About | Logout root @ PACS User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help 

There are 32 studies received this year. [Previous](#) 1 2 3 4 [Next](#) [Display All](#) Displaying 1-10 of 32 Studies

Privacy	Patient ID	Patient Name	Study ID	Date	Modalities	Accession Number	Referring Physician's Name	Received On	Source AE	Number of Images	Total Size
<input type="checkbox"/> Private <a href="#">Change to Public</a>	testsize	Testsize Testsize	<a href="#">20160317145141</a>	2016-03-17	CT	20160317145141	N/A	2016-03-17 15:40:13	SENDTOPACS	2	456.29 KB
<input type="checkbox"/> Private <a href="#">Change to Public</a>	123456	Jjjjjj Testas	<a href="#">2016010808502979</a>	2016-01-08	OT	2016010808502979	N/A	2016-03-01 17:05:20	SENDTOPACS	6	83.61 MB
<input type="checkbox"/> Private <a href="#">Change to Public</a>	123456	Jjjjjj Testas	<a href="#">2016010815545269</a>	2016-01-08	OT	2016010815545269	N/A	2016-02-10 16:13:15	SENDTOPACS	6	102.23 MB
<input type="checkbox"/> Private <a href="#">Change to Public</a>	000-00-0000	Test Test	<a href="#">15570100</a>	2009-06-22	RG	N/A	DR TEST@TEST FACILITY	2016-03-22 19:39:35	SENDTOPACS	1	4.31 MB

Check All  Forward  Delete  Export

Check All  Forward  Delete  Export

Figure 31 Statistics Report Page

## Automatic Statistics Reports via Email

If a valid SMTP server and the Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases)'s email address have been configured (See [Section 7](#) above), then MedDream PACS will send statistics report emails to the Administrator's email address based on the following schedule:

- **Daily Reports** – MedDream PACS will send statistics report for studies received during the previous day at 12:00 am local time every day

- 
- **Weekly Reports** - MedDream PACS will send statistics report for studies received during the previous week at 12:00 am local time on every Sunday
  - **Monthly Reports** - MedDream PACS will send statistics report for studies received during the previous month at 12:00 am local time on the first day of every month

### **Automatic Purging Archive Directories**

This feature is useful when the storage resources are limited on the server where MedDream PACS is installed, and the Administrators want to have MedDream PACS automatically purge older studies stored in the MedDream PACS database, by pre-defining a set of rules or parameters for automatic purging.

For Administrators (Users with 'modify' privilege), they can click on the [Automatic Purge Storage Directories](#) link from the **Tools** page to define the following set of parameters MedDream PACS:

- **Low Water Mark** – This field is defined in terms of disk free space percentage ranging from 0 to 100. For each defined archive directory, MedDream PACS will examine the disk usage information for the disk where the archive directory is located. If the disk free space percentage is lower than this defined **Low Water Mark**, MedDream PACS will start purging older studies stored on this disk.
- **High Water Mark** - This field is defined in terms of disk free space percentage ranging from 0 to 100. This field must be greater than the value defined for the **Low Water Mark** above. When the disk free space percentage drops below the **Low Water Mark** defined above, MedDream PACS will start to purge older studies stored in the corresponding archive directory. MedDream PACS will sort the list of studies stored in this archive directory by the **Date** the studies were received, with the oldest study being the top of the list. MedDream PACS will purge studies in the sorted list (removing the oldest study first) one at a time, until the disk free space percentage rises above the defined **High Water Mark**, at which point the automatic purging operation is then complete.
- **Purge by Study Received Date** (when study was received) – If this option is selected, MedDream PACS will purge all older studies that were received more than N days ago.
- **Purge by Study Date** (when study was acquired or created) – If this option is selected, MedDream PACS will purge all older studies with Study Date of more than N days ago.
- **Purge by Source AE Title** – If this option is selected, MedDream PACS will purge all studies received from the specified Source AE Title.
- **Schedule** – Automatic purging schedule defined in terms of the 24-hour interval. MedDream PACS will perform automatic purging **only** on this scheduled hour of the day, and will not perform another automatic purging for the same rule until the next 24-hour schedule.

Purge By:	<input checked="" type="radio"/> Storage Capacity: Enter Low Watermark Percentage: <input type="text" value="10"/> % Enter High Watermark Percentage: <input type="text" value="30"/> % <input type="radio"/> Study Received Date (Date When Study is Received): Purge Study Received More Than <input type="text" value="30"/> Days Ago <input type="radio"/> Study Date (Date When Study is Acquired): Purge Study Acquired More Than <input type="text" value="30"/> Days Ago <input type="radio"/> All Studies Received From This Source AE: <input type="text"/>
Run Automatic Purging Each Day At:	<input type="text" value="12"/> <input type="button" value="v"/> <input checked="" type="radio"/> A.M. <input type="radio"/> P.M.
Purge Operation:	<input checked="" type="radio"/> Delete Image Files <input type="radio"/> Move Image Files to Destination Folder: <input type="text"/> <small>(For Windows platforms, use Windows UNC format, e.g., "\\RemoteHost\RemotePath" if the destination folder specified above is a network-shared folder)</small>
Delete patient record after all studies of the patient have been purged:	<input checked="" type="radio"/> Yes <input type="radio"/> No

Figure 32 Automatic Purging Archive Directories

- Purge Option – When purging aged studies, user can select whether to:
  - Permanently delete the aged studies
  - Move them to a user-defined destination folder, for example: a shared network drive, so that they are still accessible but do not consume any more online storage resources. Note: For Windows platforms, any shared network path must be entered in the Windows UNC format as `\\RemoteHost\RemotePath\`, instead of the mapped drive path such as `Z:\LocalPath`

**NOTE:**

Caution must be taken when defining the Low/High Water Marks for the automatic purging operation, as MedDream PACS will remove all series and images of the purged study. Make sure a reasonable set of numbers is chosen for the Low/High Water Marks. By default, the Low Water Mark is set to 5 (percent) and High Water Mark set to 10 (percent). It is recommended to disable this feature if there are enough storage resources available.

**Automatic Purging By Dicom Data Element Filters**

Users can also define individual Dicom data element filter with wild-card patterns, so that MedDream PACS will automatically purge the matching Dicom studies based on the user-defined aging period and schedule.

MedDream PACS   About   Logout root @ PACS <span style="float: right;">User Administration   Configuration   Email   Journal   Home   Unread Studies   Browse   Search   Dicom AE   Auto Route   Job Status   Modality Worklist   Tools   Profile   Help </span>	
Data Element Tag:	<input type="text" value="Modality (0x00080060)"/>
Filter Pattern:	<input type="text"/>
Description:	<input type="text"/>
24-Hour Schedule:	<input type="text" value="1"/> <input type="button" value="v"/> <input checked="" type="radio"/> A.M. <input type="radio"/> P.M.
Aging Period:	Delete matching images after <input type="text" value="100"/> days
Delete patient record after all studies of the patient have been purged:	<input type="radio"/> Yes <input checked="" type="radio"/> No

Figure 33 Automatic Purging By Dicom Data Element Filter

- 
- `Data Element Tag` – Currently the following Dicom data elements are supported:
  - `Modality (0008,0060)`
    - `Institution Name (0008,0080)`
    - `Referring Physician's Name (0008,0090)`
    - `Study Description (0008,1030)`
    - `Reading Physician's Name (0008,1060)`
    - `Patient Name (0010,0010)`
  - `Filter Pattern` – This is the filtering pattern that will be used to match against the Dicom studies stored in the MedDream PACS database. Wild-card characters '\*' and '?' are supported.
  - `Description` – Brief description which described the defined filtering pattern.
  - `24-Hour Schedule` – The schedule when MedDream PACS should run the Automatic Purging by the defined Dicom data element filtering rule.
  - `Aging Period` – The time period in number of days. MedDream PACS will purge any matching Dicom study if the study was received before the defined aging period. The default value is 100 days.

For example, users can define the following Automatic Purging By Dicom Data Element rule:

- `Data Element Tag` – `Modality (0008,0060)`
- `Filter Pattern` – `CT`
- `Description` – `Purge all CT studies received more than 100 days ago`
- `24-Hour Schedule` – `1:00 AM`
- `Aging Period` – `100 Days`

With the above Automatic Purging rule, MedDream PACS will purge all CT studies stored in the database received more than 100 days ago every night at 1:00 AM local time.

### Check Duplicate Patient IDs

Clicking on this URL link will display a list of duplicate patient IDs which have conflicts with existing patient IDs. All duplicate patient IDs will have the string format of "`$(ID[$SourceAeTitle-$TimeStamp])`", where:

- `$(ID)` – The existing patient ID which has a different patient name from the duplicate
- `$(SourceAeTitle)` – The AE Title from which the images were received from
- `$(TimeStamp)` – The Date and Time stamp (in 'YYYYMMDDhhmmss' format) of when the duplicate patient ID was received

MedDream PACS | About | Logout root @ PACS      User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Database Integrity Check    Transcription Templates    Restart Service    Compress Entire Database    Statistics Reports    Export    Import    Data Element Coercion    Automatic Purge Storage Directories

Check Duplicate Patient ID    Anonymization Templates    Upload Dicom Image    Import Worklist    Today's Log    Live Monitor

There are 1 records with duplicate Patient ID of an existing record.

Previous Next      Displaying 1-1 of 1 Patients:

Limit the display of Duplicate Patient IDs by the following filter:

Check All    Forward    Delete    Export    Download    Apply Duplicate Patient ID Filter

Privacy	Patient ID	Patient Name	Date of Birth	Patient's Sex	Age	Number of Studies	Details	Duplicate
<input type="checkbox"/> Private <a href="#">Change to Public</a>	46968582ISENDTOPACS-03221939361	Joaquim Miro vi?as	N/A	N/A	N/A	1	<a href="#">More Information</a>	<a href="#">Resolve</a>

Check All    Forward    Delete    Export    Download    Apply Duplicate Patient ID Filter

Figure 34 Checking Duplicate Patient ID

For example, there is an existing patient: “Phillip B. Osterman”, with an empty patient ID string. A new study is sent by the AE ‘DICOM\_TEST’ to MedDream PACS with the same empty string as the patient ID, but with a different patient name: “Elaine J. Silverman”. In this example, MedDream PACS will save the new study under a duplicate patient ID: ‘[DICOM\_TEST-1106164654]’ and flag this as a duplicate patient ID. The user can resolve this duplicate patient ID by clicking the ‘Resolve’ link and select one of the following options:

MedDream PACS | About | Logout root @ PACS      User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Choose one of the following methods to resolve the duplicate Patient ID: (“46968582” vs. “46968582ISENDTOPACS-03221939361”)

Keep Existing Patient ID: 46968582 and Use This Patient Name:  
Firstname: JOAQUIM Lastname: MIRO VITAS

Keep Existing Patient ID: 46968582 and Use This Patient Name:  
Firstname: JOAQUIM Lastname: MIRO VITAS

Save Duplicate Using A New Patient ID:

Resolve

Figure 35 Resolving Duplicate Patient ID

- Keep Existing Patient ID and Use the Existing Patient Name – If this option is selected, the images labeled with the duplicate patient ID will be saved under the existing patient ID, and the existing patient name will be used. In the above example, the new study will be saved under the existing patient name of “Phillip B. Osterman”.
- Keep Existing Patient ID and Use the New Patient Name – If this option is selected, the images received with the duplicate patient ID will be saved under the existing patient ID, and the new patient name will be used. In the above example, the new study will be saved under the new patient name of “Elaine J. Silverman”.

- 
- **Save Duplicate Using a New Patient ID** – If this option is selected, the images labeled with the duplicate patient ID will be saved under the newly assigned patient ID, and the new patient name will be used. In the above example, the new study will be saved under the new name of 'Elaine J. Silverman' but with a newly assigned patient ID.
  - **Use Patient Names From Modality Worklist Record** – If MedDream PACS finds a Modality Worklist Record with the existing Patient ID, this option will be displayed to let users choose the Patient Names from the Modality Worklist Record, MedDream PACS will then save both the existing and duplicate Patient IDs with the Patient Names from the Modality Worklist Record.

In most cases, the duplicates are created by human input error when entering patient names. For example, "John Doe" vs. "Jane Doe", and these duplicates can be resolved by selecting either the existing patient name or the new patient name and keep the same patient ID. However, in rare cases, the duplicate patient IDs do belong to two distinct patients with truly different identities. In this case, assigning a new patient ID may help temporarily, but the ultimate solution is to fix the problem at the source, which is where the patient ID gets assigned at the local RIS/HIS systems.

### Today's Log File

Clicking on this link will display the MedDream PACS log file from today to the browser.




Figure 36 Today's Logfile Page

## Upload Dicom Image

Users with 'Upload' privilege enabled can click on this tab to upload Dicom Part-10 formatted raw images into the MedDream PACS database:





Figure 37 Upload Dicom Image Page

## Matching ORM Message (Optional)

This feature is available to users who have purchased the optional HL7 Message Listener module to enable MedDream PACS to receive and send HL7 messages. This tool can be used to select one of the received ORM (General Order) messages and match it with one or more received Dicom studies.



Patient ID	Patient Name	Date of Birth	Patient's Sex	Accession Number	Source AE	Study Date	Number of Images
<input type="checkbox"/> 1303/10	TestName	1954-05-25	F	5373	AQUILION	2016-07-06	81
<input checked="" type="checkbox"/> 1304/10	TestName	1962-12-01	F	5374	AQUILION	2016-07-06	150
<input type="checkbox"/> 1305/10	TestName	1959-02-23	F	5375	AQUILION	2016-07-06	84
<input type="checkbox"/> 1306/10	TestName	1965-04-26	F	5376	AQUILION	2016-07-06	168
<input type="checkbox"/> 1307/10	TestName	1950-04-14	F	5377	AQUILION	2016-07-06	86
<input type="checkbox"/> 1308/10	TestName	1997-05-23	F	5378	AQUILION	2016-07-06	86
<input type="checkbox"/> 1309/10	TestName	1958-11-20	M	5379	AQUILION	2016-07-06	172

Figure 38 Matching ORM Message (optional)

After the user has matched the ORM message with one of more received Dicom studies, MedDream PACS will modify the **Accession Number** and **Patient ID** of the matching Dicom studies, with the information contained in the matching ORM message. Users can also optionally select a destination Dicom AE for MedDream PACS to send

the modified Dicom studies, by selecting the destination AE from the drop-down list and checking the 'Forward modified Dicom studies to this destination AE' checkbox.

## Database Integrity Check

This feature will make MedDream PACS run an internal database integrity check where it will scan the IMAGE table of the MedDream PACS database, and verifies that for each record in the IMAGE table, the corresponding raw Dicom image file does exist and is not empty. MedDream PACS will report any missing or empty raw Dicom image file found from the integrity check.

The screenshot shows the MedDream PACS web interface. The top navigation bar includes links for 'User Administration', 'Configuration', 'Email', 'Journal', 'Home', 'Unread Studies', 'Browse', 'Search', 'Dicom AE', 'Auto Route', 'Job Status', 'Modality Worklist', 'Tools', 'Profile', and 'Help'. Below this is a secondary menu with 'Database Integrity Check' highlighted. The main content area contains a form with the following elements:

- A descriptive paragraph: "This tool will check the Image table of the MedDreamPACS-Premium database, verify that all raw Dicom images do exist and are not empty files under the archive directories."
- Two radio button options:
  - Check only the Dicom Part-10 File Header (consumes less time and resources)
  - Check the entire raw Dicom image file (consumes more time and resources)
- A checkbox labeled "Run integrity check using" followed by a text input field containing the number "5" and the text "threads simultaneously (This will make the integrity check run faster but will require more memory resource)".
- An "Integrity Check" button.

Figure 39 Database Integrity Check

## Import Worklist

This feature will make MedDream PACS import worklist records from a text file encoded in the Windows .INI format, and the imported worklist records will be inserted into the **WorkList** table in the MedDream PACS database. Then any Dicom Modality Worklist (DMWL) client can query MedDream PACS for the worklist data stored in the database.

The screenshot shows the MedDream PACS web interface with the 'Import Worklist' menu item highlighted. The main content area contains a form with the following elements:

- A descriptive paragraph: "Upload Modality Worklist from Text File(s) to MedDreamPACS-Premium".
- A file selection area with a "Browse..." button and the text "No file selected.".
- An "Upload" button.
- An "Import Worklist" button.

Figure 40 Import Worklist

The worklist text file should be formatted according to the following Windows .INI styles:

[RecordNum1]

---

Patient Name = Maximum 64 characters  
Patient ID = Maximum 64 characters  
Date of Birth = YYYY-MM-DD  
Sex = Maximum 16 characters  
Accession Number = Maximum 16 characters  
Referring Physician = Lastname^Firstname^Middlename^Prefix^Suffix (Maximum 64 characters)  
Requesting Physician = Lastname^Firstname^Middlename^Prefix^Suffix (Maximum 64 characters)  
Requested Procedure ID = Maximum 16 characters  
Requested Procedure Description = Maximum 64 characters  
Requested Procedure Priority = Maximum 16 characters  
Scheduled AE Station = Maximum 16 characters  
Modality = Maximum 16 characters  
Scheduled Start Date = YYYY-MM-DD  
Scheduled Start Time = HH:mm  
Performing Physician = Lastname^Firstname^Middlename^Prefix^Suffix (Maximum 64 characters)  
Scheduled Procedure ID = Maximum 16 characters  
Scheduled Procedure Description = Maximum 64 characters  
Scheduled Procedure Location = Maximum 16 characters  
Scheduled Procedure Pre-Medication = Maximum 64 characters  
Scheduled Procedure Contrast Agent = Maximum 64 characters  
Procedure Code Value = Maximum 16 characters  
Procedure Code Meaning = Maximum 64 characters  
Procedure Code Scheme = Maximum 16 characters  
Procedure Code Scheme Version = Maximum 16 characters  
Protocol Code Value = Maximum 16 characters  
Protocol Code Meaning = Maximum 64 characters  
Protocol Code Scheme = Maximum 16 characters  
Protocol Code Scheme Version = Maximum 16 characters

### **Live Monitor (for System Administrator only)**

When logged-in as the Administrator ('**root**' for MySQL or '**SYSTEM**' for Oracle databases), clicking on this tool will display a list of active Dicom connections (both incoming and outgoing) with MedDream PACS:

MedDream PACS | About | Logout root @ dicom

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | HL7 Application | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Database Integrity Check | Transcription Templates | Restart Service | Compress Entire Database | Statistics Reports | Export | Import | Data Element Coercion

Automatic Purge Storage Directories | Check Duplicate Patient ID | Anonymization Templates | Match ORM Message | Upload Dicom Image | Import Worklist | Today's Log | **Live Monitor**

There are currently 1 live connections:

Session ID	IP Address	Port	Source AE	Destination AE	Session Type	Patient Name	Study ID	Study Date	Start Time
81	127.0.0.1	2195	dicom_test	MultiBoot	Store	Rs-ThoraxOriginal	Anonymized with	2005-02-22	2007-09-18 09:54:13

Figure 41 Live Monitor page

## Patient Reconciliation

If the **Automatic Patient Reconciliation** feature is enabled by the Administrator ('root' for MySQL or 'SYSTEM' for Oracle databases) (described in [Section 0](#)), MedDream PACS will log automatic patient reconciliation events in the table shown below, which contains the following information for each event:

- When – Date and time of when the event took place
- Patient ID – Patient ID of the subject patient
- Date of Birth – DOB of the subject patient
- Original Patient Name – Original patient name before the event took place
- Modified Patient Name – Modified patient name after the event took place

MedDream PACS | About | Logout root @ dicom

User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | HL7 Application | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help

Database Integrity Check | Transcription Templates | Restart Service | Compress Entire Database | Statistics Reports | Export | Import | Data Element Coercion | Automatic Purge Storage Directories

Check Duplicate Patient ID | Anonymization Templates | Match ORM Message | **Patient Reconciliation** | Upload Dicom Image | Import Worklist | Today's Log | Live Monitor

When	Patient ID	Date of Birth	Study ID	Original Patient Name	Modified Patient Name
------	------------	---------------	----------	-----------------------	-----------------------

Figure 42 Patient Reconciliation Page

## Anonymization Templates

For some client sites, e.g., clinical trials, users may want to anonymize all the patient demographics information, e.g., Patient Name, Patient ID, Date of Birth, etc., to meet the HIPAA Patient Privacy requirements. In such cases, users can pre-define a template with a set of specific syntax rules for MedDream PACS to anonymize the corresponding Dicom data elements in the received studies, by clicking on the **Tools->Anonymization Templates** page from the Main Menu to add or modify a template for anonymization of the received Dicom studies.

The following Dicom data elements can be defined in the Anonymization Template:

- **Patient Name** (0x00100010)

- **Patient ID** (0x00100020)
- **Date of Birth** (0x00100030)
- **Gender** (0x00100040)
- **Patient's Age** (0x00101010)
- **Study ID** (0x00200010)
- **Referring Physician's Name** (0x00080090)
- **Study Description** (0x00081030)
- **Series Description** (0x0008103E)

The following macros can be used to define the anonymization syntax for the Dicom **Patient ID** (0x00100020) data element:

- **\$MD5\$** – MedDream PACS will anonymize the Dicom Patient ID data element with the MD-5 hash string of the original value. The resulting new Patient ID will be a fixed 32-char hex number string.
- **\$STUDYUID\$** – MedDream PACS will replace the value of the Dicom Patient ID data element with the current value of the **Study Instance UID (0020,000D)** data element. NOTE: This anonymization implies that every anonymized study will be stored under a different Patient ID, which is the same as the Study Instance UID of that study.

MedDream PACS v6.5.2   Admin   Logout user @ HSCA		User Administration   Configuration   Home   Admin   Home   User and Studies   Browse   Search   Current All   Audit Results   Job Status   Metadata Workflow   Tools   Profile   Help	
Enter Anonymization Syntax Name:			
Date Element: Patient Name (0x00100010)	Anonymization Syntax:	Anonymized	
	Syntax Description:		
Date Element: Patient ID (0x00100020)	Anonymization Syntax:	EMF5G	
	Syntax Description:		
Date Element: Date of Birth (0x00100030)	Anonymization Syntax:	18700101	
	Syntax Description:		
Date Element: Patient's Address (0x00101040)	Anonymization Syntax:	Anonymized	
	Syntax Description:		
Date Element: Patient's Sex (0x00101040)	Anonymization Syntax:	Anonymized	
	Syntax Description:		
Date Element: Age (0x00101010)	Anonymization Syntax:	BODY	
	Syntax Description:		
Date Element: Study ID (0x00200010)	Anonymization Syntax:	Anonymized	
	Syntax Description:		
Date Element: Institution Name (0x00080030)	Anonymization Syntax:	Anonymized	
	Syntax Description:		
Date Element: Institution Address (0x0008003E)	Anonymization Syntax:	Anonymized	
	Syntax Description:		

Data Element: Referring Physician's Name (040008090)	Anonymization System: Anonymized System Description:
Data Element: Study Description (040001010)	Anonymization System: Anonymized System Description:
Data Element: Performing Physician's Name (040008050)	Anonymization System: Anonymized System Description:
Data Element: Reading Physician's Name (040008060)	Anonymization System: Anonymized System Description:
Data Element: Operator's Name (040006100)	Anonymization System: Anonymized System Description:
Data Element: Series Description (040001020)	Anonymization System: Anonymized System Description:

Add

Figure 43 Anonymization Templates

Once the anonymization templates are defined, the users can select which template to use for anonymizing Dicom studies received from a source AE from the **"edit"** menu of the Application Entity page (see [Section 0](#) for more details).

### Transcription Templates (Windows platforms only)

For Windows platforms, the Administrator can upload Microsoft Word document templates with pre-configured bookmarks (and/or with company letterhead) and assign this pre-defined template to a particular Source AE, so that when the web users are entering study notes for a subject Dicom study received from that Source AE, they can download this pre-defined Word document template with the pre-configured bookmarks automatically filled-in by MedDream PACS with the corresponding information from the Dicom study.

For example, the following bookmarks in the Anonymization Template Microsoft Word document can be pre-configured to be automatically filled-in by MedDream PACS with the corresponding information from the Dicom study:

- **PatientName** – This bookmark will be auto-filled with the Patient Name (0x00100010) information from the subject Dicom study
- **PatientID** – This bookmark will be auto-filled with the Patient ID (0x00100020) information from the subject Dicom study
- **DateOfBirth** – This bookmark will be auto-filled with the Date of Birth (0x00100030) information from the subject Dicom study
- **StudyDate** – This bookmark will be auto-filled with the Study Date (0x00200010) information from the subject Dicom study
- **ReferDoc** – This bookmark will be auto-filled with the Referring Physician's Name (0x00080090) information from the subject Dicom study

Enter Transcription Template Name:	Bookmark:	Description:
Upload Transcription Template (Word Document) (This Word template will contain the following bookmarks)	Bookmarks: PatientID	Description: [Text Input]
Enter Bookmark Name for: Patient ID	Bookmarks: PatientID	Description: [Text Input]
Enter Bookmark Name for: Study ID	Bookmarks: StudyID	Description: [Text Input]
Enter Bookmark Name for: Study Date	Bookmarks: StudyDate	Description: [Text Input]
Enter Bookmark Name for: Referring Physician's Name	Bookmarks: RefPhys	Description: [Text Input]
Enter Bookmark Name for: Institution Name	Bookmarks: InstitutionName	Description: [Text Input]
Enter Bookmark Name for: Study Description	Bookmarks: StudyDescription	Description: [Text Input]
Enter Bookmark Name for: Patient's Sex	Bookmarks: Gender	Description: [Text Input]

Figure 44 Transcription Template (Windows platforms only)

## Restart Service

For users with the **System Administration** privilege enabled, this page will be displayed to allow the System Administrators to restart the Dicom Server component as well as the optional HL7 Interface of MedDream PACS (if enabled). However, the **<Restart>** button will be available only if there is no active connection to/from MedDream PACS, i.e., if there is any active connection to/from MedDream PACS, the list of active connections will be displayed instead of the **<Restart>** button.

## Profile Page

This page allows users to modify their profile information, which include:

- User's names, password and email address information
- Preferred import source directory
- Preferred import source media drive
- Preferred import destination folder
- Preferred export directory
- Whether or not to share notes about a subject Dicom study or image
- Customizable study view columns to be displayed in study list pages
- Customizable patient view columns to be displayed in patient list pages
- Number of records to be displayed in multi-page web user interface pages (default is 10)

Save: see profile for user

Change User's Password	New password for current user (must be at least 8 characters and include 1 number, 1 capital letter and 1 special character from "!"@#\$%)	****
Enter Preferred Import Directory	If defined, the Preferred Import Directory will be displayed instead of the system default import directory when importing files to MedDreamPACS-Prepium	
Enter Preferred Import Removable Media Drive	If defined, the Preferred Import Removable Media Drive will be displayed instead of the system default when importing from removable media to MedDreamPACS-Prepium	
Enter Preferred Import Destination Folder	If defined, the Preferred Import Destination Folder will be displayed instead of the system default when importing from removable media to MedDreamPACS-Prepium	
Enter Preferred Export Directory	If defined, the Preferred Export Directory will be displayed instead of the system default export directory when exporting files from the MedDreamPACS-Prepium	
Show Study/Study Notes	Enabled; other users will be able to modify the notes entered by this user about a subject study or image	<input type="checkbox"/> Yes <input checked="" type="checkbox"/> No
Customize Study Views	Select the study information to be displayed for the Study List pages	<input checked="" type="checkbox"/> Patient ID <input checked="" type="checkbox"/> Patient Name <input checked="" type="checkbox"/> Patient's Sex <input checked="" type="checkbox"/> Date of Birth <input checked="" type="checkbox"/> Age <input checked="" type="checkbox"/> Institution Name <input checked="" type="checkbox"/> Study ID <input checked="" type="checkbox"/> Study Date <input checked="" type="checkbox"/> Study Time <input checked="" type="checkbox"/> Accession ID <input checked="" type="checkbox"/> Accession Number <input checked="" type="checkbox"/> Referring Physician's Name <input checked="" type="checkbox"/> Description <input checked="" type="checkbox"/> Referring Physician's Name <input checked="" type="checkbox"/> Request ID <input checked="" type="checkbox"/> Requesting Physician's Name <input type="checkbox"/> Storage Commitment Report <input type="checkbox"/> Source AC <input type="checkbox"/> Modality <input type="checkbox"/> Admitting Diagnosis <input type="checkbox"/> Interpretation Author <input type="checkbox"/> Law System <input type="checkbox"/> Verified By
Customize Patient Views	Select the information to be displayed for the Patient List pages	<input checked="" type="checkbox"/> Patient ID <input checked="" type="checkbox"/> Patient Name <input checked="" type="checkbox"/> Date of Birth <input checked="" type="checkbox"/> Patient's Sex <input checked="" type="checkbox"/> Age <input type="checkbox"/> Institution Name <input type="checkbox"/> Issue of Patient ID
Customize Views Page Size	Enter the number of items that will be displayed in each view page	10
Show Study Notes URL Link	If enabled, a URL-linked Study Notes icon will be displayed in the checkbox column in front of each subject study	<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Unsave Refresh Period	Enter the time interval in seconds for automatically refresh unsaved events	60

Modify

Figure 45 User Profile Page

### Modality Worklist Page

This page displays the Dicom Modality Worklist (DMWL) data that is currently stored in the MedDream PACS database, which contains the following tabbed pages:

- Today's Worklist - This page displays the worklist data for all procedures scheduled today
- Yesterday's Worklist - This page displays the worklist data for all procedures that were scheduled yesterday
- This Week's Worklist - This page displays the worklist data for all procedures scheduled this week
- This Month's Worklist - This page displays the worklist data for all procedures scheduled this month
- Last Month's Worklist - This page displays the worklist data for all procedures that were scheduled last month
- Enter New Worklist - This page allows the user to enter the Dicom Modality Worklist data manually into the database



Forward the following Patient:

0

Please select which Application Entity to forward to: SENDTOPACS ▾

Please select forwarding schedule:

Immediately

At this hour: 12:00 AM ▾

Select Source AE Title:

Use Current AE Title of MedDreamPACS-Premium

Use This AE Title:

Figure 48 Forwarding Images

Users can select the destination AE from the drop-down list of remote SCP's., which are defined in the *Application Entity Table* described in [Section 0](#) above. Clicking on the '**Forward**' button will schedule a database job to forward the selected patient(s), study(s) or series to the selected destination AE. The scheduled database job will then be processed by the MedDream PACS DICOM Server component, where all stored images of the selected patient(s), study(s) or series are transmitted to the destination AE.

To find out if the selected patient(s), study(s) or series have been successfully forwarded to the destination AE, the user can click on the '[Job Status](#)' link in the *Main Menu* bar, which is described in detail in the [Job Status Page](#) below.

## Post-Receive Image Compression

When delivering Dicom images to remote web browser (e.g., Java Applet viewers or Active-X plug-in), especially via a WAN connection, users often find the need for speeding up the image transfer between the MedDream PACS and the remote browsers. If this is the case, the Administrator can enable the Post-Receive Image Compression feature of MedDream PACS for each source AE, by selecting one of the Dicom compression transfer syntaxes from the list below:

- **JPEG Lossless Transfer Syntax** – If this value is selected, MedDream PACS will compress any received image using the Dicom JPEG Lossless Compression (Selection Value 1, Process 14) transfer syntax (UID 1.2.840.10008.1.2.4.70), and will save the compression image with the “.1s” filename extension.
- **JPEG Lossy Transfer Syntax** – If this value is selected, MedDream PACS will compress any received image using the Dicom JPEG Baseline Lossy Compression transfer syntax (UID 1.2.840.10008.1.2.4.50) for 8-bit images, and the Dicom JPEG Extended Lossy Compression transfer syntax (UID 1.2.840.10008.1.2.4.51) for 12-bit images. Both types of compressed images will be saved with the “.1y” filename extension. The image quality of the lossy compression is controlled by the following setting for each source AE if this transfer syntax is selected:

Compress images received from this AE	<ul style="list-style-type: none"><li>• Select Dicom Compression Transfer Syntax: <input type="text" value="JPEG Lossless Transfer Syntax"/></li><li>• Compression ratio if JPEG2000 Lossy transfer syntax is selected, e.g., 20 (for 20:1), 10 (for 10:1), 5 (for 5:1), etc.: <input type="text"/></li><li>• Compressed image quality if either JPEG Lossy or JPEG2000 Lossy transfer syntax is selected, e.g., 90 (for 90%), 80 (for 80%), etc.: <input type="text"/></li></ul>
---------------------------------------	---

Figure 49 Compression Setting for JPEG Lossy Transfer Syntax

The quality can be set to 1 (worst quality, best compression ratio) to 100 (best quality, least compression ratio). The default value of 90 (percent) will be used if the above setting is absent.

- **Runtime Length Encoding (RLE) Transfer Syntax** – If this value is selected, MedDream PACS will compress any received image using the Dicom RLE compression transfer syntax (UID 1.2.840.10008.1.2.5), and will save the compression image with the “.rle” filename extension.
- **JPEG2000 Part-1 Lossless Only Transfer Syntax** – If this value is selected, MedDream PACS will compress any received image using the Dicom JPEG2000 Part-1 Lossless Only transfer syntax (UID 1.2.840.10008.1.2.4.90), and will save the compression image with the “.j2k” filename extension.
- **JPEG2000 Part-1 Lossless Or Lossy Transfer Syntax** – If this value is selected, MedDream PACS will compress any received image using the Dicom JPEG2000 Part-1 Lossless Or Lossy transfer syntax (UID 1.2.840.10008.1.2.4.91), and will save the compression image with the “.j2k” filename extension. The compression ratio or image quality of the JPEG2000 lossy compression are controlled by the following settings for each source AE if this transfer syntax is selected:

Compress images received from this AE	<ul style="list-style-type: none"><li>• Select Dicom Compression Transfer Syntax: <input type="text" value="JPEG2000 Part-1 Lossless Or Lossy Transfer Syntax"/></li><li>• Compression ratio if JPEG2000 Lossy transfer syntax is selected, e.g., 20 (for 20:1), 10 (for 10:1), 5 (for 5:1), etc.: <input type="text"/></li><li>• Compressed image quality if either JPEG Lossy or JPEG2000 Lossy transfer syntax is selected, e.g., 90 (for 90%), 80 (for 80%), etc.: <input type="text"/></li></ul>
---------------------------------------	---

Figure 50 Compression Setting for JPEG2000 Part-1 Lossless or Lossy Transfer Syntax

---

The compression ratio can be set to 20 (20:1), 10 (10:1), 5 (5:1), etc. with higher compression ratio generally leading to lesser image quality. The image quality can be set to 1 (worst quality, best compression ratio) to 100 (best quality, least compression ratio), and the default quality is 90 (percent).

With the above Post-Receive Image Compression feature enabled, MedDream PACS will first check if any of the compressed images is available when delivering Dicom images to the web browsers, and will prefer the compressed images over the original images when transferring the images to the remote browsers. By default, MedDream PACS uses the Lossless mode of the JPEG2000 Lossless or Lossy compression if both of the above Registry settings are absent.

---

## Automatic Routing

### Dicom Image Routing

In addition to forwarding patient(s), study(s) or series manually from the MedDream PACS web user interface, users can define automatic routing table entries to forward images automatically based on the following criteria:

- **Source AE Title** – This is the AE title from where the images are received. If the **Route By Source AE Title** option is selected and an image is received from the matching source AE title, MedDream PACS will route the received image to the defined destination AE automatically, according to the routing schedule defined below.
- **Key Attribute Tag** – Currently the following list of Dicom attributes are supported:
  - Institution Name - (0008,0080)
  - Referring Physician Name - (0008,0090)
  - Patient ID - (0010,0020)
  - Protocol Name - (0018,1030)
  - Performing Physician's Name (0008,1050)
  - Reading Physician's Name (0008,1060)
  - Operator's Name (0008,1070)
  - Study Description (0008,1030)
  - Series Description (0008,103E)
  - Accession Number (0008,0050)
  - Modality (0008,0060)
  - Modalities In Study (0008,0061)

If the **Route By Key Attribute** option is selected, users can define a **Key Matching Pattern** string (may include wild-card characters including '\*' and '?') to match against received image attribute tags. If the key attribute tag in the received image matches with the specified matching pattern string, MedDream PACS will route the received image to the defined destination AE automatically, according to the routing schedule defined below.

- **By Applying the Logical AND Operator (&&) to Both Criteria Above** – If this option is selected, MedDream PACS will apply both the **Source AE Title** and **Key Attribute Tag** criteria using the logical AND (&&) operator, i.e., the received images must match **both** the defined **Source AE Title** and **Key Attribute Tag** pattern before they can be forwarded to the defined Destination AE.
- **By Applying the Advanced Logical Expressions** – Users can configure advanced logical expressions for the automatic routing rule, which consists of one or more key matching patterns against the routing key attributes above, as well as logical operators such as **AND (&&)**, **OR (| |)**. Users can also specify the priority for applying multiple logical expressions by using the round brackets "()", i.e., logical expressions enclosed within the round brackets will be applied first, before those expressions outside of the round brackets. For more information about this feature, please refer to the advanced logical expression example below.
- **Destination AE Title** – This is the AE title where the images will be sent.

- 
- **Copy To Destination Folder** – If this option is selected, MedDream PACS will copy received images into the specified destination folder, instead of forwarding them to a destination AE.
  - **Hourly Schedule** – Automatic forwarding schedule by the 24-hour clock, which can be either '**Immediately**', a [**From, To**] spread window, a specified 24-hour clock interval, or a [**From, To**] immediate-filter window.
  - **Weekly Schedule** – Automatic forwarding schedule by the 7-weekday daily schedule. The weekly schedule is combined with the hourly schedule above to determine when or if MedDream PACS should forward the received images.
  - **Purge After Routing** – Whether or not MedDream PACS should purge the received images automatically after they have been routed successfully to the destination AE.
  - **Forward Existing [n] Oldest Studies To Destination AE** – If this checkbox is selected, MedDream PACS will also forward the [n] existing oldest studies to the destination AE, in addition to the newly received study. If a negative number (e.g., "-1") is entered, MedDream PACS will forward the [n] existing newest/latest studies to the destination AE, in addition to the newly received study.
  - **Wait [n] minutes for all instances of the study to be received, and forward the entire study instead of individual images** – If this checkbox is selected, MedDream PACS will wait the specified [n] minutes for all images of the study to be received, then forward the entire study via a single Dicom association to the destination AE and transfer all images of the study.
  - **Wait [n] minutes for all instances of the series to be received, and forward the entire series instead of individual images** – If this checkbox is selected, MedDream PACS will wait the specified [n] minutes for all images of the series to be received, then forward the entire series via a single Dicom association to the destination AE and transfer all images of the series.
  - **Retry Interval for retrying failed automatic routing jobs** – This time interval (in hours) specify the amount of delay MedDream PACS will wait before attempting to retry a failed job. The default value is 0, which means MedDream PACS will attempt to retry any failed job as soon as it fails.
  - **Do not use the AE Title assigned to MedDream PACS** – If this checkbox is selected, MedDream PACS will use either the Original/Source AE Title from the source AE, or the User-specified AE Title (instead of using the AE Title configured for MedDream PACS) when sending images to the destination AE.

When specifying the AE titles for automatic routing entries, the source and destination AE titles are used as keys to the routing table, which implies that one source AE can have one (uni-cast) or more (multi-cast) destination AE (s) associated with the routing entry. In other words, received images from the same source AE can be forwarded to multiple destinations AE (s) if there are more than one destination AE (s) defined for the source AE.

- If '**Immediately**' is specified as the schedule for the automatic routing table, then images will be forwarded to the destination AE (s) as soon as they are received.
- If a '**From**' and '**To**' Spread Window is specified as the schedule for the automatic routing table, then MedDream PACS will forward any received images to the destination AE (s), by choosing an hourly schedule that is evenly distributed across the specified [**From, To**] Spread Window. This scheduling option is useful when users want to spread the automatic routing jobs evenly across the [**From, To**] window, thus avoid making any hour particularly busy with too many routing jobs.
- If a fixed 24-hour clock interval is used, then the received images will be forwarded at the specified hour. For example, if the schedule is set to 9:00 P.M., then the received images will not be forwarded to the destination AE (s) until the local time is 9:00 P.M. If there are any images received between 9:00 P.M. and 9:59 P.M., they will be forwarded immediately, and images received after 9:59 P.M. will be forwarded the next day at 9:00 P.M.
- If a '**From**' and '**To**' Immediate-Filter Window is specified as the schedule for the automatic routing table, then images will be forwarded to the destination AE (s) immediately if the local time is within the specified [**From, To**] Immediate-Filter Window.




Figure 51 Automatic Dicom Image Routing

Example routing rules:

- Route By Source AE Title – Users can click on the **By Source Application Entity** option and enter the following parameters:

Source AE Title - Scanner  
 Destination AE Title - eFilm  
 Hourly Schedule - Immediately  
 Weekly Schedule - Any day  
 Auto Purge - No

With the above routing rule, all images received from the AE “Scanner” will be automatically routed to AE “eFilm” as soon as they are received. The received images will be kept in MedDream PACS database after they are routed to the destination AE “eFilm”.

- Route By Key Attribute – Users can click on the **By Key Attribute** option and enter the following parameters:

Key Attribute Tag - Referring Physician’s Name (0008,0090)  
 Matching Pattern - John D\*  
 Destination AE Title - DCMTK  
 Hourly Schedule - 1:00 A.M.  
 Weekly Schedule - Tuesday  
 Auto Purge - Yes

With the above routing rule, all images received with the referring physician name such as “John Doe” or “John David” will be automatically routed to AE “DCMTK” at 1:00 A.M local time on Tuesdays. (However, received images with referring physician name such as “Dr. John Doe” or “Mr. John David” do not match with the

---

defined routing pattern string and therefore will not be routed.) The received images will be purged after they have been routed successfully to the destination AE "DCMTK".

- **Route By Advanced Logical Expressions** – Users can use the following button tools to build the advance logical expression pattern string:
  - **Left Round Bracket** – Clicking on this button will append "(" to the logical expression pattern.
  - **Right Round Bracket** – Clicking on this button will append ")" to the logical expression pattern.
  - **AND (&&)** – Clicking on this button will append "&&" to the logical expression pattern.
  - **OR (||)** – Clicking on this button will append "||" to the logical expression pattern.
  - **Key Attribute Tag** – Supported routing key Dicom attribute tag, e.g. , Referring Physician's Name (0008,0090).
  - **Matching Pattern** – Pattern string to be matched with the current value of the key attribute above. Wild-card characters such as '\*' and '?' are supported. If the pattern is prefixed by the '!' character, then the logical NOT (!) operator will be applied for the pattern string defined for this Dicom key attribute.
  - **Append** – Clicking on this button will append the "%\$tag=\$pattern%" string above to the current logical expression, where \$tag is the Dicom key attribute tag and \$pattern is the matching pattern specified above.
  - **Reset** – Clicking on this button will clear or reset the current logical expression pattern string.

For example, the logical expression "(%00080090=smith\*% OR %00100020=12345\*) AND %00080060=ct%" will match the received Dicom studies with the following criteria:

- Any Referring Physician's Name (0008,0090) beginning with "smith" or Patient ID (0010,0020) beginning with "12345", **AND**
- Modality (0008,0060) is CT

So a received Dicom CT study with the Referring Physician's Name of "Smith^John" would match with this routing rule, while a MR study with the Patient ID of "123456" would not match.

To find out if the statuses of the automatically routed images and check whether they have been successfully sent to the destination AE(s), the user must login as the Administrator/Super-user account ('root' for MySQL or 'SYSTEM' for Oracle databases) and click on the 'Job Status' link in the Main Menu bar. This is because the automatic routing jobs are internal System level properties and do not belong to any particular user, therefore they should be maintained only by the system administrator.

If for any reason (e.g., no receiving application is accepting images at the destination AE) the automatically routed images cannot be delivered successfully, MedDream PACS will retry up to a maximum of three (default) attempts to deliver the failed images to the destination AE. This **Maximum Retries** parameter is configurable by modifying the following Windows Registry value:

```
HKEY_LOCAL_MACHINE\Software\Softneta\MedDream PACS\{AETITLE}\MaximumRetries
```

Where:

{AETITLE} is the Application Entity Title you have assigned for MedDream PACS during installation.

---

## HL7 Message Routing (optional)

If the HL7 Message Listener option is installed, users can define automatic routing table entries to forward received HL7 messages automatically based on the following criteria:

**Source Application Name** – This is the HL7 application from where the messages are received. If the **Route By Source Application Name** option is selected and a message is received with the matching “**Sending Application**” field in the **MSH** Message Header, MedDream PACS will route the received messages to the defined destination HL7 application automatically, based to the routing schedule defined below.

- **Key in Message Header** – Currently the following keys are supported:

- **Message Type**
- **Receiving Application**
- **Receiving Facility**
- **Sending Facility**

If this option is selected, users can define a **Key Matching Pattern** string (may include wild-card characters such as '\*' or '?') to match against the **MSH** message header in the received HL7 messages. If the key attribute in the received messages matches with the specified matching pattern, MedDream PACS will route the received messages to the defined destination HL7 application automatically, according to the routing schedule defined below.

- **Destination Application** – This is the destination HL7 application where the received messages will be sent.
- **Schedule** – Automatic forwarding schedule, which can be either '**Immediately**', a [**From, To**] 24-hour clock window, or a specified 24-hour clock interval:
  - **Immediately** - Messages will be forwarded to the destination HL7 application (s) as soon as they are received.
  - '**From**' and '**To**' Schedule Window - Messages will be forwarded to the destination HL7 application (s) when the current time is within the specified [**From, To**] Schedule Window.
  - **Fixed 24-hour clock interval** - Messages will be forwarded at the specified hour. For example, if the schedule is set to 9:00 P.M., then the received messages will not be forwarded to the destination HL7 application (s) until the local time is 9:00 P.M. If there are any messages received between 9:00 P.M. and 9:59 P.M., they will be forwarded immediately, and messages received after 9:59 P.M. will be forwarded the next day at 9:00 P.M.

Once a routing entry is defined, all HL7 Messages received from the SOURCE Application will automatically be forwarded to the DESTINATION Application with the specified SCHEDULE.

By Source Application Name:  (Wild-Card Characters \* and ? Are Supported)

Select Routing Criteria:  By This Key in Message:

with Case-Insensitive Matching Pattern:  (Wild-Card Characters \* and ? Are Supported)

Enter Destination HL7 Application:

Enter Routing Schedule:  Immediately (As soon as received)

From:  To:

Fixed At:   A.M.  P.M.

Figure 52 Automatic HL7 Message Routing (optional)

## Printing Images

When navigating through the patients, studies, series and images stored in the MedDream PACS database, if the current user has the 'Print' privilege enabled, a 'Print' button will be displayed to allow current user to print the selected patients, studies or series to a remote destination Dicom Printer/Print SCP:

Print the following study to [Apfa.DSS300: D55302](#)  
4365183

Number of Copies	<input type="text" value="1"/>
Orientation	<input checked="" type="radio"/> Portrait <input type="radio"/> Landscape
Image Display Format	<input checked="" type="radio"/> Standard: <input type="text" value="2"/> Rows by <input type="text" value="2"/> Columns <input type="radio"/> R1,R2,R3 Rows <input type="text"/> <input type="radio"/> C1,C2,C3 Columns <input type="text"/> <input type="radio"/> 35mm Slides <input type="radio"/> 40mm Slides <input type="radio"/> Printer Custom Format <input type="text"/>
Polarity	<input checked="" type="radio"/> Normal <input type="radio"/> Reverse
Print Priority	<input type="radio"/> LOW <input checked="" type="radio"/> MEDIUM <input type="radio"/> HIGH
Print Medium	<input checked="" type="radio"/> Paper <input type="radio"/> Clear Film <input type="radio"/> Blue Film
Film Size ID	<input checked="" type="radio"/> Default <input type="radio"/> 8-Inch x 10-Inch <input type="radio"/> 10-Inch x 12-Inch <input type="radio"/> 11-Inch x 14-Inch <input type="radio"/> 14-Inch x 14-Inch <input type="radio"/> 14-Inch x 17-Inch
Film Destination	<input checked="" type="radio"/> Magazine <input type="radio"/> Processor <input type="radio"/> Bin: <input type="text"/>
Annotation Display Format	<input checked="" type="checkbox"/> Box 1 - Upper-Left Corner <input type="text" value="%PATIENTNAME% %PATIENTID% %PATIENTBIRTHDATE% %PATIENTSEX%"/> <input type="checkbox"/> Box 2 - Lower-Left Corner <input type="text"/> <input checked="" type="checkbox"/> Box 3 - Upper-Left Corner Below Annotation Box 1 <input type="text" value="%STUDYID%"/> <input checked="" type="checkbox"/> Box 4 - Upper-Left Corner Below Annotation Box 3 <input type="text" value="%STUDYDATE%"/> <input type="button" value="Server Manager"/>

Figure 53 Printing to Remote Dicom Printer

From the above **Print** menu page, users can select the destination Dicom printer and choose the following printing parameters:

- Number of copies
- Film orientation
- Image display format (can be printer specific)
- Print priority (if supported by remote printer)
- Print medium
- Film destination
- Convert color images to grayscale (if applicable) – If the images being printed are a mixture of both color and grayscale images, users can choose whether or not to convert all color images to grayscale before sending them to the Dicom printer which may not support printing color images

# Job Status Page

The current status of all database jobs submitted by the current user are displayed by clicking on the 'Job Status' link of the Main Menu bar in the Job Status page, with the 'Completed' jobs displayed first followed by 'Failed' database jobs.

If the current logged-in user has the 'Modify' privilege, then there will be a 'Retry' button as well as a 'Delete' button displayed in this page if there is any failed job. User can select the job (s) to delete or retry by clicking on the checkbox in front of the job ID column and pressing either the 'Delete' button or the 'Retry' button.

MedDream PACS | About | Logout root @ PACS    User Administration | Configuration | Email | Journal | Home | Unread Studies | Browse | Search | Dicom AE | Auto Route | Job Status | Modality Worklist | Tools | Profile | Help    Sofneta

**My Submitted Jobs:**

0 completed jobs. Completed jobs will be deleted after a period of 24 hours

4 pending or failed jobs. Failed jobs will be deleted after a period of 24 hours

Previous Next    Displaying 1-4 of 4 Jobs:

ID	Username	AE Title	Type	Class	Universally Unique ID (UUID)	Schedule	Priority	Submit Time	Start Time	Finish Time	Status	Retries	Details	Retry Interval	N/A
<input type="checkbox"/> 1	root	Testinis	Forward	study	<a href="#">Patient Name: Sunys</a> <a href="#">Sendopacs</a> <a href="#">Study ID: demo</a> <a href="#">Accession Number: demo</a>	Immediately	Medium	2016-06-13 15:04:15	N/A	N/A	submitted	0	N/A	0	N/A
<input type="checkbox"/> 2	root	Testinis	Forward	study	<a href="#">Patient Name: Sunys</a> <a href="#">Sendopacs</a> <a href="#">Study ID: demo</a> <a href="#">Accession Number: demo</a>	Immediately	Medium	2016-06-13 15:04:20	N/A	N/A	submitted	0	N/A	0	N/A
<input type="checkbox"/> 3	root	N/A	export	study		Immediately	N/A	2016-06-13 15:04:51	N/A	N/A	submitted	0	C:/MedDreamPACS-Premium/MedDream/med-dream/tmp/20160613150451410914.export.tmp	0	N/A
<input type="checkbox"/> 4	root	Testinis	Forward	study	<a href="#">Patient Name: Sunys</a> <a href="#">Sendopacs</a> <a href="#">Study ID: demo</a> <a href="#">Accession Number: demo</a>	Immediately	Medium	2016-06-13 15:25:20	N/A	N/A	submitted	0	N/A	0	N/A

**Other User's Jobs:**

Figure 54 Job Status Page

- Id – Job ID which is generated automatically by the MySQL database
- User – The username which created the database job
- AeTitle – Destination AE title
- Type – Job type, e.g., 'Forward', 'Print', etc.
- Level – Hierarchy level, e.g., 'Patient', 'Study', 'Series', etc.
- UID – Unique ID in the hierarchy level, e.g., patient ID, study UID, series UID, etc.
- SubmitTime – Timestamp on when the database job is submitted
- StartTime – Timestamp on when the database job starts processing
- FinishTime – Timestamp on when the database job finishes processing
- Status – Success or Failure
- Details – Any detailed errors if the database job has failed

---

## Figures

Figure 1 User Accounts Administration.....	17
Figure 2 Creating New User Account.....	18
Figure 3 Creating Group User Accounts .....	20
Figure 4 Modifying Existing User Account.....	21
Figure 5 System Configuration Page .....	24
Figure 6 Configuring SMTP Server .....	26
Figure 7 System Journal Log .....	27
Figure 8 Adding a New Application Entity .....	31
Figure 9 Application Entity Table Page .....	32
Figure 10 Search Remote PACS Database .....	34
Figure 11 HL7 Applications (optional) .....	38
Figure 12 Search MedDream PACS Database.....	39
Figure 13 Login Page.....	40
Figure 14 Home Page (Today's Study Page).....	41
Figure 15 Unread Studies Page.....	42
Figure 16 Browse Page.....	42
Figure 17 Study Page .....	43
Figure 18 Series Page .....	45
Figure 19 Add Study Notes.....	46
Figure 20 Study Notes Page.....	46
Figure 21 Structured Report Page .....	47
Figure 22 Image Page (Thumbnail).....	48
Figure 23 Image Page (Full Size).....	49
Figure 24 Add Image Notes .....	50
Figure 25 Image Notes Page .....	51
Figure 26 Online Image Processing Page.....	52
Figure 27 Tools Page.....	53
Figure 28 Data Element Coercion Page.....	53
Figure 29 Export Patients/Studies Page .....	55
Figure 30 Warning Message for Importing without DICOMDIR.....	56
Figure 31 Statistics Report Page.....	57

---

Figure 32 Automatic Purging Archive Directories.....	59
Figure 33 Automatic Purging By Dicom Data Element Filter.....	59
Figure 34 Checking Duplicate Patient ID.....	61
Figure 35 Resolving Duplicate Patient ID.....	61
Figure 36 Today's Logfile Page.....	62
Figure 37 Upload Dicom Image Page.....	63
Figure 38 Matching ORM Message (optional).....	63
Figure 39 Database Integrity Check.....	64
Figure 40 Import Worklist.....	64
Figure 41 Live Monitor page.....	66
Figure 42 Patient Reconciliation Page.....	66
Figure 43 Anonymization Templates.....	68
Figure 44 Transcription Template (Windows platforms only).....	69
Figure 45 User Profile Page.....	70
Figure 46 Modality Worklist Page.....	71
Figure 47 Enter New Worklist Page.....	71
Figure 48 Forwarding Images.....	72
Figure 49 Compression Setting for JPEG Lossy Transfer Syntax.....	73
Figure 50 Compression Setting for JPEG2000 Part-1 Lossless or Lossy Transfer Syntax.....	73
Figure 51 Automatic Dicom Image Routing.....	77
Figure 52 Automatic HL7 Message Routing (optional).....	80
Figure 53 Printing to Remote Dicom Printer.....	81
Figure 54 Job Status Page.....	82

---

## **Tables**

<i>Table 1 Revisions</i> .....	13
<i>Table 2 MedDream PACS User Privileges</i> .....	19
<i>Table 3 MedDream PACS User Categories</i> .....	19
<i>Table 4 Options Specific for Group Users</i> .....	20
<i>Table 5 Application Entity Table</i> .....	31
<i>Table 6 Data Element Coercion Rule Patterns</i> .....	54

---

# Index

## A

AE Group Settings: .....	37
Anonymization Templates .....	66
Application Entity Table .....	29
Automatic Monthly System Journal Log Emails .....	28
Automatic Purging Aged System Journal Log .....	28
Automatic Purging Archive Directories .....	58
Automatic Purging By Dicom Data Element Filters .....	59
Automatic Routing .....	75
Automatic Statistics Reports via Email .....	57

## B

Browse Page .....	42
-------------------	----

## C

Change log .....	10
Check Duplicate Patient IDs .....	60
Contents .....	3
Creating Group User Accounts .....	20
Creating New User Accounts .....	17
Custom Data Element Coercion .....	53

## D

Database Integrity Check .....	64
Deleting Existing User Accounts .....	20
Dicom Image Routing .....	75

## E

Enter New Worklist Page .....	71
Explanation of symbols used .....	7
Exporting Patients/Studies .....	55

## F

Forwarding Images .....	71
-------------------------	----

## G

Glossary .....	9
----------------	---

## H

HL7 Applications (optional) .....	38
-----------------------------------	----

---

HL7 Message Routing (optional) .....	79
Home Page (Today's Study Page) .....	41

**I**

Image Notes Page .....	50
Image Page (Full Size) .....	49
Image Page (Thumbnail) .....	48
Import Worklist.....	64
Importing External Patients/Studies .....	56
Installation .....	15
Introduction .....	8

**J**

Job Status Page .....	82
-----------------------	----

**L**

Live Monitor (for System Administrator only) .....	65
Login Page.....	40

**M**

Main Menu Bar .....	41
Managing MedDream PACS User Accounts .....	16
Matching ORM Message (Optional).....	63
Modality Worklist Page.....	70
Modality Worklist SCP Application Entities: .....	35
Modifying Existing User Accounts.....	21

**N**

Navigating MedDream PACS Web User Interface.....	40
Notes on the user`s manual.....	6

**O**

Online Image Processing Page .....	52
------------------------------------	----

**P**

Patient Reconciliation .....	66
Platforms .....	14
Post-Receive Image Compression .....	73
Pre-Fetching of Dicom Studies for Scheduled AE Station .....	36
Printing Images .....	80
Privacy Attributes .....	16
Profile Page.....	69
Purpose and availability of documentation .....	6

---

## Q

Query/Retrieve SCP Application Entities: .....	36
Questions and comments .....	6

## R

Restart Service .....	69
-----------------------	----

## S

SCP Application Entities .....	34
SCU Application Entities.....	32
Searching MedDream PACS Database .....	39
Series Page.....	45
System Configuration.....	22
System Journal Log .....	27
SMTP Server Configuration .....	26
Statistics Reports .....	57
Structured Reports .....	47
Study Notes Page.....	46
Study Page .....	43

## T

Today's Log File.....	62
Tools Page.....	53
Transcription Templates (Windows platforms only).....	68

## U

Unread Studies Page.....	42
Upload Dicom Image .....	63

---

MedDream PACS is manufactured by Softneta UAB.

Medical device class: Directive 93/42/EEC

Class I medical device

ID of the notified body: 191352247

**Softneta UAB**

K. Barsausko str. 59  
51423 Kaunas, Lithuania

